

Serie IP44 Low voltage

IP44 Low-voltage plugs & sockets

Reference : 00312

IP44 Combo socket 3P+E 380V 16A 6H (2 sockets)



Features

Application:	Electrical connection
Apto para instalación en exterior:	No
Type of installation:	Wall-mounting
Intensidad nominal (A):	16
Voltage (V):	380/415
Frecuency (Hz):	50/60
Number of poles:	3P+T
Time code:	6
Color:	Red

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Glow wire resistance (°C):	960
Ball pressure test (°C):	125

Additional features

Cable flexible (mm ²):	1-2,5
Cable rígido (mm ²):	1-4
Inversor de fase:	No

Materials

Plastic parts material:	PA6 (Polyamide 6)
Contact material:	Copper-zinc alloy
Materiales libres de halógenos:	Yes

Fields for ETIM

Modelo ETIM:	Suspendido
--------------	------------

Certificates and regulations

Directive:	2011/65/EU
Norms:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Suministro:	Supplied in an individual box per packaging multiple.
Type d'emballage:	NE
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	5
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.044 x 0.185 x 0.285
Package weight (kg):	0.432
Peso bruto unitario (kg):	0.475

Codes

EAN code GETIM13:	8431044003122
Tariff code:	85366990
ETIM 8.0 Code:	EC004118
Código ETIM 9.0:	EC004118

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
---	---------------------



Packaging:	100% recyclable cardboard
-------------------	---------------------------

Downloads (links)

Assembly instructions:	91208
-------------------------------	-------