

Serie IP44 Low voltage

IP44 Low-voltage plugs & sockets

Reference : 01106

IP44 Wander plug 3P+N+E 110V 32A 4H



Features

Application:	Electrical connection
Apto para instalación en exterior:	No
Type of installation:	Mobile
Intensidad nominal (A):	32
Voltage (V):	57/100-75/130
Frecuency (Hz):	50/60
Number of poles:	3P+N+T
Time code:	4
Color:	Yellow

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Glow wire resistance (°C):	960
Ball pressure test (°C):	125

Additional features

Cable flexible (mm ²):	2,5-6
Inversor de fase:	No

Materials

Plastic parts material:	PA6 (Polyamide 6)
Contact material:	Copper-zinc alloy
Materiales libres de halógenos:	Yes

Fields for ETIM

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Suministro:	Supplied in an individual box per packaging multiple.
Type d'emballage:	NE
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	10
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.018 x 0.23 x 0.32
Package weight (kg):	0.241
Peso bruto unitario (kg):	0.265

Codes

EAN code GETIM13:	8431044011066
Tariff code:	85366990
ETIM 8.0 Code:	EC000140
Código ETIM 9.0:	EC000140

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/01106.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/01106.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/01106.pdf>

Assembly instructions: 91208