

Serie IP44-IP67 Interlocking

IP44-IP67 Interlocking sockets

Reference : 01814

IP66 - IP67 Flush-fit interlocking socket 2P+E 110V 32A 4H



Features

Application:	Electrical connection
Apto para instalación en exterior:	Yes
Type of installation:	Flush-fit
Intensidad nominal (A):	32
Voltage (V):	100/130
Frecuency (Hz):	50/60
Number of poles:	2P+T
Time code:	4
Color:	Yellow

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (°C):	960
Ball pressure test (°C):	125

Additional features

Cable flexible (mm ²):	2,5-6
Cable rígido (mm ²):	2,5-10
Inversor de fase:	No

Materials

Plastic parts material:	PA6 (Polyamide 6)
Contact material:	Copper-zinc alloy
Materiales libres de halógenos:	Yes

Fields for ETIM

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Suministro:	Supplied in an individual box per packaging multiple.
Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.13 x 0.104 x 0.19
Package weight (kg):	0.666
Peso bruto unitario (kg):	0.733

Codes

EAN code GETIM13:	8431044018140
Tariff code:	85366990
ETIM 8.0 Code:	EC001324
Código ETIM 9.0:	EC001324

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/01814.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/01814.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/01814.pdf>

Assembly instructions: 91208