

Serie IP67 Low voltage

IP67 Low-voltage plugs & sockets

Reference : 03756P

IP67 Wander socket 3P+N+E 380V 125A 6H pilot contact



Features

Application:	Electrical connection
Apto para instalación en exterior:	Yes
Type of installation:	Mobile
Intensidad nominal (A):	125
Voltage (V):	200/346-240/415
Frecuency (Hz):	50/60
Number of poles:	3P+N+T
Time code:	6
Color:	Red

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (°C):	960
Ball pressure test (°C):	125

Additional features

Cable flexible (mm ²):	16-50 / 1-2,5
Inversor de fase:	No

Materials

Plastic parts material:	PA6 (Polyamide 6)
Contact material:	Copper-zinc alloy
Materiales libres de halógenos:	Yes

Fields for ETIM

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Suministro:	Supplied in an individual box per packaging multiple.
Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	2
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.16 x 0.255 x 0.325
Package weight (kg):	1.514
Peso bruto unitario (kg):	1.665

Codes

EAN code GETIM13:	8431044037578
Tariff code:	85366990
ETIM 8.0 Code:	EC001320
Código ETIM 9.0:	EC001320

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Assembly instructions:

91208