

Serie Atlantic Combinable

IP30-IP40 Combinable steel surface distribution cabinets. (48-192 modules)

Reference : 40ENL72-96

IP40 Combinable surface distribution cabinet without door (72-96 mod.)



Features

Application:	Tertiary (large facilities)
Apto para instalación en exterior:	No
Type of installation:	Surface
Piece dimensions Height x Width x Depth (mm):	710 x 670 x 212
Capacity/Number of modules:	72-96
Calidad del material:	Rolled steel

Technical data

Protection degree:	IP30
Resistance to impact:	IK07

Dimensions

Piece dimensions Height x Width x Depth (mm):	710 x 670 x 212
Cable entry - WidthxDepth (mm):	440x106
Usable inner space - Height (mm):	650 x 0 x 0

Additional features

Capacity/Number of modules:	72-96
Door/window/lid type:	Sin puerta
Reversible door:	No
Body type:	Combinable
Lock type:	Doble barra 5
Plate:	No
Placa ajustable:	No
Placa perforada:	No
No. locks:	2
Closure - No. of points:	1 point
Cierre - Tipo llave:	5 mm double-bit Polyamide key included
Modelo mural apoyado:	No
Módulo en esquina:	No
Montaje intermedio:	No
Tejadillo inclinado:	No
Additional Information:	IP30 (Without door) / IP40 (With door); IK07 (Without door) / IK09 (With transparent door) / IK10 (With opaque door)

Materials

Lock material:	Poliamida
Seal material:	Polyurethane
Color:	WhiteRAL 9003
Acabado:	Embossed hardened polyester paint
Body thickness (mm):	1.2
Top/bottom panel thickness (mm):	1.2

Maximum loads

Total maximum load (kg): 30

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Intensidad nominal (A): Up to 630 (depending on type of accessory).

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)

20	25	30	35	40
124.9	156.2	187.4	218.6	249.9

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.705 x 0.675 x 0.089

Package weight (kg): 15.214

Peso bruto unitario (kg): 16.735

Codes

EAN code GETIM13:	8431044280769
Tariff code:	85381000
ETIM 8.0 Code:	EC000058
Código ETIM 9.0:	EC000058

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/40ENL72-96.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/40ENL72-96.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/40ENL72-96.pdf
Assembly instructions:	92853