


Serie -

Reference : 42594

Plastic site distribution board IP65 1x12 modules single-phase
40A



Features

Application:	Construction
Apto para instalación en exterior:	Yes
Type of installation:	Wall-mounting
Calidad del material:	ABS

Modular capacity

Capacity/Number of modules:	1x12
Number of rows:	1

Technical data

Protection degree:	IP65
Resistance to impact:	IK08
Box glow wire resistance (°C):	650
Glow wire resistance in sockets (°C):	960
Double insulation:	Class II

Dimensions

Piece dimensions Height x Width x Depth (mm):	436 x 345 x 210
---	-----------------

Additional features

Emergency button:	Yes Associated with undervoltage coil
-------------------	---------------------------------------

Door/window/lid type:	Transparente
Reversible door:	No
UV protection:	Yes
Lock type:	Cierre a presión
No. locks:	1
Sealable:	Yes
Enlazable:	Yes
Incorpora Raíl DIN:	Yes

Materials

Materiales libres de halógenos:	Yes
Base material:	ABS
Frame material:	ABS
Door/window/lid material:	Polycarbonate (PC)
Lock material:	Resina acetática
Color:	Grey RAL 7035
Door color:	Tinted

Electrical properties

Voltage (V):	230
Intensidad nominal (A):	40
Type of switch:	Single-phase

Certificates and regulations

Packaging

Suministro:	Supplied fully assembled according to the specifications of each reference, protected with shrink wrap and packed in multiple cardboard packaging according to the number of units ordered.
Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.46 x 0.365 x 0.115

Codes

EAN code GETIM13: 8431044425948

Tariff code: 85371098

ETIM 8.0 Code: EC000484

Código ETIM 9.0: EC000484

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Downloads (links)

Assembly instructions: 93064