

Serie -

RF60 Fire protection doors

Reference : 60RF4550

Fire-resistant access panel RF60 450x500 mm



Features

Application:	Fire-resistant enclosures
Apto para instalación en exterior:	No
Type of installation:	Flush-fit
Tipo de producto:	Registro cortafuegos

Technical data

Protection degree:	IP43
Resistencia al fuego:	Yes
Degree of fire resistance:	EI260
Resistance to impact:	IK10

Dimensions

Piece dimensions Height x Width x Depth (mm):	497 x 547 x 22.5
hueco_empotrar_alto_ancho_profundo_mm:	455 x 505 x 22

Additional features

Door/window/lid type:	Opaca única
Reversible door:	No
Lock type:	Triángulo 8
Plate:	No
No. of doors:	1

No. locks:	2
Additional Information:	Sealable closure according to REBT

Materials

Calidad del material:	Rolled steel
Lock material:	Acero cincado
Plate material:	Silica sand,Fiberglass
Hinge material:	Stainless steel
Materiales libres de halógenos:	No
Color:	WhiteRAL 9003
Acabado:	Embossed hardened polyester paint

Electrical properties

Maximum voltage (V):	1000 V / AC
----------------------	-------------

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 13501-2; UNE-EN 1634-1

Packaging

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.513 x 0.565 x 0.044
Package weight (kg):	6.216
Peso bruto unitario (kg):	6.837

Codes

EAN code GETIM13:	8431044291000
-------------------	---------------

Tariff code:	85381000
ETIM 8.0 Code:	EC000747
Código ETIM 9.0:	EC000747

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/60RF4550.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/60RF4550.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/60RF4550.pdf
Assembly instructions:	92835