

Serie -

-

Reference : AB55100/CB



Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Surface
Tipo de producto:	Registro secundario

Technical data

Protection degree:	IP33
Resistencia al fuego:	No
Resistance to impact:	IK07

Dimensions

Piece dimensions Height x Width x Depth (mm):	600 x 1050 x 150
---	------------------

Additional features

Door/window/lid type:	Opaca única
Reversible door:	Yes
Lock type:	Tipo buzón con llave
Plate:	Yes
Plate type:	Wood
No. of doors:	1
No. locks:	2

Materials

Calidad del material:	Rolled steel
Lock material:	Poliamida
Plate material:	Wood
Materiales libres de halógenos:	No
Color:	WhiteRAL 9003
Acabado:	Embossed hardened polyester paint
Plate thickness (mm):	10

Electrical properties

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.615 x 1.065 x 0.17
Package weight (kg):	16.209
Peso bruto unitario (kg):	17.83

Codes

EAN code GETIM13:	8431044110202
Tariff code:	85381000
ETIM 8.0 Code:	EC000374
Código ETIM 9.0:	EC000374

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/AB55100CB.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/AB55100CB.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/AB55100CB.pdf
Assembly instructions:	91210