

Serie -

-

Reference : AE55100



Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Flush-fit
Tipo de producto:	Registro secundario

Technical data

Protection degree:	IP33
Resistencia al fuego:	No
Resistance to impact:	IK07

Dimensions

Piece dimensions Height x Width x Depth (mm):	596 x 1046 x 150
hueco_empotrar_alto_ancho_profundo_mm:	570 x 1020 x 160

Additional features

Door/window/lid type:	Opaca doble
Reversible door:	No
Lock type:	Doble barra 5
Plate:	Yes
Plate type:	Water-repellent
No. of doors:	2

No. locks: 2

Materials

Calidad del material: Rolled steel

Lock material: Poliamida

Plate material: Moisture-resistant wood

Materiales libres de halógenos: No

Color: WhiteRAL 9003

Acabado: Embossed hardened polyester paint

Plate thickness (mm): 10

Electrical properties

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.62 x 1.115 x 0.056

Package weight (kg): 11.073

Peso bruto unitario (kg): 12.18

Codes

EAN code GETIM13: 8431044275703

Tariff code: 85381000

ETIM 8.0 Code: EC000374

Código ETIM 9.0:	EC000374
-------------------------	----------

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/AE55100.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/AE55100.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/AE55100.pdf
Assembly instructions:	92815