

Serie -

-

Reference : AF4545



Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Surface
Tipo de producto:	Registro de enlace

Technical data

Protection degree:	IP55
Resistencia al fuego:	No
Resistance to impact:	IK10
Glow wire resistance (°C):	650

Dimensions

Piece dimensions Height x Width x Depth (mm):	500 x 500 x 150
---	-----------------

Additional features

Door/window/lid type:	Opaca única
Reversible door:	No
Lock type:	Doble barra 5
Plate:	No
No. of doors:	1
No. locks:	2

Materials

Calidad del material:	Rolled steel
Lock material:	Poliamida
Materiales libres de halógenos:	No
Color:	Grey RAL 7035
Acabado:	Embossed hardened polyester paint

Electrical properties

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.52 x 0.515 x 0.17
Package weight (kg):	9.718
Peso bruto unitario (kg):	10.69

Codes

EAN code GETIM13:	8431044276007
Tariff code:	85381000
ETIM 8.0 Code:	EC000374
Código ETIM 9.0:	EC000374

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
---	---------------------

Packaging: 100% recyclable cardboard

Downloads (links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/AF4545.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/AF4545.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/AF4545.pdf>