

Serie -

-

Reference : AM4545



Features

Application:	Telecommunications
Apto para instalación en exterior:	Yes
Type of installation:	Surface
Tipo de producto:	Registro secundario

Technical data

Protection degree:	IP55
Resistencia al fuego:	No
Resistance to impact:	IK10

Dimensions

Piece dimensions Height x Width x Depth (mm):	500 x 500 x 150
---	-----------------

Additional features

Door/window/lid type:	Opaca única
Reversible door:	Yes
Body type:	Compact
Lock type:	Doble barra 5
Plate:	Yes
Plate type:	Wood
No. of doors:	1

No. locks: 2

Materials

Calidad del material: Rolled steel

Lock material: Poliamida

Plate material: Wood

Materiales libres de halógenos: No

Color: Grey RAL 7035

Acabado: Embossed hardened polyester paint

Plate thickness (mm): 10

Electrical properties

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.52 x 0.515 x 0.17

Package weight (kg): 12.153

Peso bruto unitario (kg): 13.368

Codes

EAN code GETIM13: 8431044275000

Tariff code: 85381000

ETIM 8.0 Code: EC000374

Código ETIM 9.0:

EC000374

Environmental

Fecha verificación sustancias SVHC (reach):

0000-00-00 00:00:00

Packaging:

100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):

<https://ide.es/docs/planos/stp/AM4545.stp>

Product drawing DXF (URL):

<https://ide.es/docs/planos/dxf/AM4545.dxf>

Product drawing (PDF):

<https://ide.es/docs/planos/pdf/AM4545.pdf>