


Serie Argenta Plus. Accessories

IP55-IP65 Steel floor-standing cabinets accessories

Reference : BFP19/15U

Profils for partial fixed frame rack 19' 15U for 600/800 cabinet depth (2-piece pack)



Features

Series compatibility:	ARGENTA PLUS ENL - ARMARIO AUTOPORTANTE
Product compatibility:	For 600/800-mm wide cabinet.
Apto para instalación en exterior:	No

Additional features

Assembly units:	15
Placa perforada:	No
Placa ajustable:	No
Reversible door:	No
Plate:	No

Dimensions

Technical data

Electrical properties

Materials

Calidad del material:	Zinc plated steel
Materiales libres de halógenos:	No

Thickness (mm):	2
Templado:	No

More information

Characteristics:	For assembly in 600mm wide cabinets, it is necessary to request 1 unit of the PME reference depending on the depth of the cabinet if they are placed in the upper / lower part of the cabinet, or 2 units if they are placed at any other height. To be installed in 800 mm wide cabinets, it is necessary to request: - 1 unit of the PME reference depending on the depth of the cabinet if they are placed at the top / bottom of the cabinet or 2 units if they are placed at any other height. - 1 unit of reference PME800 (width). - 1 unit of reference SBFP19.
Technical data:	Assembly units: 15 U. Highly resistant triple-fold profiles. With cut-outs for 19" devices on both sides, on the front and the side of the cabinet.

Certificates and regulations

Packaging

Type d'emballage:	WR
U.M. Embalaje - Unitario:	PK
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.035 x 0.75 x 0.06
Package weight (kg):	1.579
Peso bruto unitario (kg):	1.737

Codes

EAN code GETIM13:	8431044435909
Tariff code:	85381000
ETIM 8.0 Code:	EC002518
Código ETIM 9.0:	EC002518

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
---	---------------------

Downloads (Links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/BFP1915U.stp>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/BFP1915U.pdf>

Assembly instructions: 90392