

# Serie Argenta Plus BIG-INOX

IP65 Stainless steel floor-standing compact cabinets

**Reference : BIG18016040POD/INX**

Stainless steel floor-standing double door cabinet  
1800x1600x400 with mounting plate



## Features

|                                               |                                      |
|-----------------------------------------------|--------------------------------------|
| Application:                                  | Corrosive environments,Food industry |
| Apto para instalación en exterior:            | No                                   |
| Type of installation:                         | Floor-standing                       |
| Piece dimensions Height x Width x Depth (mm): | 1800 x 1600 x 400                    |
| Calidad del material:                         | AISI 304 stainless steel             |

## Technical data

|                            |       |
|----------------------------|-------|
| Protection degree:         | IP55  |
| NEMA degree of protection: | 1, 12 |
| Resistance to impact:      | IK10  |

## Dimensions

|                                               |                   |
|-----------------------------------------------|-------------------|
| Piece dimensions Height x Width x Depth (mm): | 1800 x 1600 x 400 |
| Cable entry - WidthxDepth (mm):               | 500x200           |

## Additional features

|                          |                                                                                            |
|--------------------------|--------------------------------------------------------------------------------------------|
| Door/window/lid type:    | Opaca doble                                                                                |
| Reversible door:         | Yes                                                                                        |
| No. of doors:            | 2                                                                                          |
| Body type:               | Compact                                                                                    |
| Lock type:               | Maneta de palanca + cilindro perfilado doble barra                                         |
| Plate:                   | Yes                                                                                        |
| Plate type:              | Plain                                                                                      |
| Placa ajustable:         | Yes                                                                                        |
| Placa perforada:         | No                                                                                         |
| No. of hinges:           | 4                                                                                          |
| No. locks:               | 1                                                                                          |
| Closure - No. of points: | 4 points                                                                                   |
| Cierre - Tipo llave:     | 5 mm double-bit Inactive door with internal 2-point locking. Profile cylinder not included |
| Modelo mural apoyado:    | Yes                                                                                        |
| Módulo en esquina:       | No                                                                                         |
| Montaje intermedio:      | No                                                                                         |
| Tejadillo inclinado:     | No                                                                                         |

## Materials

|                                 |                              |
|---------------------------------|------------------------------|
| Lock material:                  | Zamak                        |
| Plate material:                 | Galvanised steel             |
| Seal material:                  | Polyurethane                 |
| Acabado:                        | Satin finish with Scotch 320 |
| Body thickness (mm):            | 1.5                          |
| Door thickness (mm):            | 2                            |
| Plate thickness (mm):           | 3                            |
| Cable entry lid thickness (mm): | 2                            |

## Maximum loads

## Electrical properties

**Maximum voltage (V):** 1000 AC / 1500 DC

**Intensidad nominal (A):** Up to 3200 (depending on type of accessory).

**Power dissipation:**

Power dissipation P(W) as a function of temperature increase  $\Delta T$  (°C)

| 20    | 25    | 30     | 35     | 40     |
|-------|-------|--------|--------|--------|
| 648.6 | 855.8 | 1026.9 | 1198.1 | 1369.3 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

## Certificates and regulations

**Directive:** 2014/35/EU

**Norms:** UNE-EN 62208, UNE-EN 61439-1

## Packaging

**Type d'emballage:** PF

**U.M. Embalaje - Unitario:** C62

**Minimum amount of sale:** 1

**dimensiones\_embalaje\_unitario\_alto\_ancho\_prof\_m:** 1.92 x 1.65 x 0.55

**Package weight (kg):** 200.146

**Peso bruto unitario (kg):** 220.16

## Codes

|                   |               |
|-------------------|---------------|
| EAN code GETIM13: | 8431044486932 |
| Tariff code:      | 85381000      |
| ETIM 8.0 Code:    | EC000261      |
| Código ETIM 9.0:  | EC000261      |

## Environmental

|                                             |                           |
|---------------------------------------------|---------------------------|
| Fecha verificación sustancias SVHC (reach): | 0000-00-00 00:00:00       |
| Packaging:                                  | 100% recyclable cardboard |

## Downloads (links)

|                            |                                                                                                                         |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Product drawing STP (URL): | <a href="https://ide.es/docs/planos/stp/BIG18016040PODINX.stp">https://ide.es/docs/planos/stp/BIG18016040PODINX.stp</a> |
| Product drawing DXF (URL): | <a href="https://ide.es/docs/planos/dxf/BIG18016040PODINX.dxf">https://ide.es/docs/planos/dxf/BIG18016040PODINX.dxf</a> |
| Product drawing (PDF):     | <a href="https://ide.es/docs/planos/pdf/BIG18016040PODINX.pdf">https://ide.es/docs/planos/pdf/BIG18016040PODINX.pdf</a> |