

Serie Small Distribution Boxes

Small distribution boxes

Reference : BT4

IP20 Surface distribution box 4 modules sealable



Features

Application:	Domestic
Apto para instalación en exterior:	No
Type of installation:	Surface
Calidad del material:	Polystyrene (PS)

Modular capacity

Capacity/Number of modules:	1x4
Number of rows:	1

Technical data

Protection degree:	IP20
Resistance to impact:	IK08
Glow wire resistance (°C):	650
Ball pressure test (°C):	70
Double insulation:	Class II

Dimensions

Piece dimensions Height x Width x Depth (mm):	130 x 85 x 64
---	---------------

Additional features

Door/window/lid type:	Sin tapa
-----------------------	----------

Reversible door:	No
UV protection:	No
Tipo de cubierta:	None
Sealable:	No
Enlazable:	No
Neutral and earth bars:	No
Incorpora Raíl DIN:	Yes
Plate:	No
Placa ajustable:	No
Placa perforada:	No

Materials

Materiales libres de halógenos:	Yes
Base material:	Polystyrene (PS)
Frame material:	Polystyrene (PS)
Base colour:	WhiteRAL 9003
Frame color:	WhiteRAL 9003

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)

20	25	30	35	40
2.7	3.3	4.0	4.7	5.3

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 24

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.007 x 0.31 x 0.42

Package weight (kg): 0.099

Peso bruto unitario (kg): 0.108

Codes

EAN code GETIM13: 8431044241500

Tariff code: 85381000

ETIM 8.0 Code: EC000214

Código ETIM 9.0: EC000214

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)
