

Serie Ecology

IP65 Distribution boxes

Reference : CDP36PT3F

IP65 PC distribution box 3x12 (36) modules



Features

Application:	Industrial (Watertight and distribution enclosures),Renewable energies
Apto para instalación en exterior:	Yes
Type of installation:	Surface
Calidad del material:	Polycarbonate (PC)

Modular capacity

Capacity/Number of modules:	3x12 (36)
Number of rows:	3

Technical data

Protection degree:	IP65
Resistance to impact:	IK08
Glow wire resistance (°C):	850
Ball pressure test (°C):	70
Temperatura máxima materiales (°C):	+80
Double insulation:	Class II

Dimensions

Piece dimensions Height x Width x Depth (mm):	586 x 310 x 148
Upper cable entry (mm):	8xM20-2xM25-2xM32-1xM40
Bottom cable entry (mm):	6xM20-2xM25-2xM32-1xM40

Inner cable entry (mm):	4xM25
Rear oblong:	2xOB 25/32/25

Additional features

Door/window/lid type:	Transparente
Reversible door:	Yes
UV protection:	Yes
No. of doors:	1
Lock type:	Cierre a presión
No. locks:	2
Cierre - Tipo llave:	Without key Possibility of lock with key (ref. 92150) or 8 mm triangular lock (ref. 22069), available as optional accessories
Tipo de cubierta:	Door
Versión de la cubierta:	Closed
Sealable:	Yes
Enlazable:	Yes
Neutral and earth bars:	No
Incorpora Raíl DIN:	Yes
Plate:	No
Placa ajustable:	No
Placa perforada:	No

Materials

Materiales libres de halógenos:	Yes
Base material:	Polycarbonate (PC)
Frame material:	Polycarbonate (PC)
Door/window/lid material:	Polycarbonate (PC)
Lock material:	Resina acetálica
Base colour:	Grey RAL 7035
Frame color:	Grey RAL 7035
Door color:	Tinted

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)

20	25	30	35	40
33.2	41.5	49.8	58.1	66.5

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 2

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.596 x 0.315 x 0.167

Package weight (kg): 3.234

Peso bruto unitario (kg): 3.557

Codes

EAN code GETIM13: 8431044130354

Tariff code: 85381000

ETIM 8.0 Code: EC000214

Código ETIM 9.0: EC000214

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/CDP36PT3F.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/CDP36PT3F.pdf>

Assembly instructions: 92809