

Serie -

-

Reference : COM1208020/BMP

Metal site distribution board IP65 4x16 (64) modules three-phase 160A



Features

Application:	Construction
Apto para instalación en exterior:	No
Type of installation:	Wall-mounting
Calidad del material:	Rolled steel

Modular capacity

Capacity/Number of modules:	4x16 (64)
Number of rows:	4

Components:

Nº	Description	IP	Poles	Current (A)	Voltage (V)
2	Interlocking sockets	67	3P+N+T	32	400
1	Interlocking socket	67	3P+T	32	400
2	Interlocking sockets	67	3P+N+T	16	400
1	Interlocking socket	67	3P+T	16	400
2	Interlocking socket	67	2P+T	16	230
4	Schuko-type sockets	67	2P+TT	16	230
1	Crane base	67	3P+N+T	63	400
1	Emergency stop button	65	-	-	-

Protections:

Nº	Description	Curve	Rated breaking capacity (kA)	Rated residual current (mA)	Poles	Current (A)	Voltage (V)
1	MCB miniature circuit breaker	C	10	-	3P	32	400
1	MCB miniature circuit breaker	C	10	-	3P	16	400
4	MCB miniature circuit breakers	C	10	-	2P	16	230
2	MCB miniature circuit breakers	C	10	-	4P	16	400
2	MCB miniature circuit breakers	C	10	-	4P	32	400
1	MCB miniature circuit breaker	C	10	-	4P	63	400
2	RCCB residual current circuit breakers	AC	-	30	2P	40	230
1	RCCB residual current circuit breaker	AC	-	30	4P	40	400
3	RCCB residual current circuit breakers	AC	-	30	4P	63	400
1	General Switch (IGA)	C	10	-	4P	160	400

Technical data

Protection degree:	IP65
Resistance to impact:	IK08
Glow wire resistance in sockets (°C):	960

Dimensions

Piece dimensions Height x Width x Depth (mm):	1200 x 995 x 270
---	------------------

Additional features

Emergency button:	Yes Associated with undervoltage coil
Door/window/lid type:	Opaca
Reversible door:	No
UV protection:	Yes
Lock type:	Doble barra 5
No. locks:	4
Sealable:	No
Enlazable:	No

Incorpora Raíl DIN:	No
---------------------	----

Materials

Materiales libres de halógenos:	No
Lock material:	Poliamida
Color:	Grey RAL 7035
Acabado:	Embossed hardened polyester paint

Electrical properties

Voltage (V):	230/400
Intensidad nominal (A):	160
Type of switch:	Three-phase

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 61439-1; UNE-EN 61439-4 (en los requisitos

Packaging

Suministro:	- Supplied fully assembled according to the specifications of each reference. - Packed in individual cardboard packaging.
Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	1.22 x 1.025 x 0.115
Package weight (kg):	74.357
Peso bruto unitario (kg):	81.793

Codes

EAN code GETIM13:	8431044220581
Tariff code:	85371098

ETIM 8.0 Code: EC000484

Código ETIM 9.0: EC000484

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Assembly instructions: 93064