

Serie -

-

Reference : COM808020/BMP

Metal site distribution board IP65 6x16 (96) modules three-phase 80A



Features

Application:	Construction
Apto para instalación en exterior:	No
Type of installation:	Wall-mounting
Calidad del material:	Rolled steel

Modular capacity

Capacity/Number of modules:	6x16 (96)
Number of rows:	6

Components:

Nº	Description	IP	Poles	Current (A)	Voltage (V)
1	Interlocking socket	67	3P+N+T	32	400
1	Interlocking socket	67	3P+T	32	400
1	Interlocking socket	67	3P+N+T	16	400
1	Interlocking socket	67	3P+T	16	400
2	Interlocking sockets	67	2P+T	16	230
4	Schuko-type sockets	67	2P+TT	16	230
1	Emergency stop button	65	-	-	-

Protections:

Nº	Description	Curve	Rated breaking capacity (kA)	Rated residual current (mA)	Poles	Current (A)	Voltage (V)
1	MCB miniature circuit breaker	C	10	-	4P	32	400
1	MCB miniature circuit breaker	C	10	-	3P	32	400
1	MCB miniature circuit breaker	C	10	-	4P	16	400
1	MCB miniature circuit breaker	C	10	-	3P	16	400
4	MCB miniature circuit breakers	C	10	-	2P	16	230
1	RCCB residual current circuit breaker	AC	-	30	4P	63	400
1	RCCB residual current circuit breaker	AC	-	30	4P	40	400
2	RCCB residual current circuit breaker	AC	-	30	2P	40	230
1	General Switch (IGA)	C	10	-	4P	80	400

Technical data

Protection degree: IP65

Resistance to impact: IK08

Glow wire resistance in sockets (°C): 960

Dimensions

Piece dimensions Height x Width x Depth (mm): 800 x 835 x 270

Additional features

Emergency button: Yes Associated with undervoltage coil

Door/window/lid type: Opaca

Reversible door: No

UV protection: Yes

Lock type: Doble barra 5

No. locks: 2

Sealable: No

Enlazable: No

Incorpora Raíl DIN: No

Materials

Materials libres de halógenos:	No
Lock material:	Poliamida
Color:	Grey RAL 7035
Acabado:	Embossed hardened polyester paint

Electrical properties

Voltage (V):	230/400
Intensidad nominal (A):	80
Type of switch:	Three-phase

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 61439-1; UNE-EN 61439-4 (en los requisitos

Packaging

Suministro:	- Supplied fully assembled according to the specifications of each reference. - Packed in individual cardboard packaging.
Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.82 x 0.855 x 0.115
Package weight (kg):	47.459
Peso bruto unitario (kg):	52.205

Codes

EAN code GETIM13:	8431044220574
Tariff code:	85371098
ETIM 8.0 Code:	EC000484

Código ETIM 9.0:	EC000484
-------------------------	----------

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
--	---------------------

Packaging:	100% recyclable cardboard
-------------------	---------------------------

Downloads (links)

Assembly instructions:	93064
-------------------------------	-------