

# Serie Domos-Kjunction

Junction boxes for hollow walls

**Reference : CT1515/PH**

IP33 flush-fit junction box hollow walls 134x134x61



## Features

|                                    |                        |
|------------------------------------|------------------------|
| Application:                       | Domestic               |
| Apto para instalación en exterior: | No                     |
| Type of installation:              | Flush-fit hollow walls |
| Calidad del material:              | Polystyrene (PS)       |

## Modular capacity

## Technical data

|                            |     |
|----------------------------|-----|
| Glow wire resistance (°C): | 850 |
|----------------------------|-----|

## Dimensions

|                                               |                |
|-----------------------------------------------|----------------|
| Piece dimensions Height x Width x Depth (mm): | 153 x 153 x 64 |
| hueco_empotrar_alto_ancho_profundo_mm:        | 134 x 134 x 61 |

## Additional features

|                                  |                   |
|----------------------------------|-------------------|
| Door/window/lid type:            | Opaca atornillada |
| Sujeción de puerta/tapa/ventana: | Screw-on          |
| Reversible door:                 | No                |
| UV protection:                   | No                |
| No. of doors:                    | 1                 |
| Lock type:                       | Con tornillos     |

---

|                                |             |
|--------------------------------|-------------|
| <b>Tipo de cubierta:</b>       | Cover       |
| <b>Versión de la cubierta:</b> | Blind cover |
| <b>Sealable:</b>               | No          |
| <b>Enlazable:</b>              | No          |
| <b>Neutral and earth bars:</b> | No          |
| <b>Incorpora Raíl DIN:</b>     | No          |
| <b>Plate:</b>                  | No          |
| <b>Placa ajustable:</b>        | No          |
| <b>Placa perforada:</b>        | No          |

---

## Materials

---

|                                        |                  |
|----------------------------------------|------------------|
| <b>Materiales libres de halógenos:</b> | Yes              |
| <b>Base material:</b>                  | ABS              |
| <b>Door/window/lid material:</b>       | Polystyrene (PS) |
| <b>Color:</b>                          | WhiteRAL 9003    |
| <b>Base colour:</b>                    | WhiteRAL 9003    |

---

## Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)

| 20  | 25  | 30  | 35  | 40  |
|-----|-----|-----|-----|-----|
| 2.7 | 3.4 | 4.1 | 4.8 | 5.5 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

## Certificates and regulations

## Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 56

dimensiones\_embalaje\_unitario\_alto\_ancho\_prof\_m: 0.153 x 0.153 x 0.064

Package weight (kg): 0.182

Peso bruto unitario (kg): 0.2

## Codes

EAN code GETIM13: 8431044564265

Tariff code: 85381000

ETIM 8.0 Code: EC002601

Código ETIM 9.0: EC002601

## Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

## Downloads (links)

Assembly instructions: 91452