

Serie Domos-Kjunction

Junction boxes for hollow walls

Reference : CT1522/PH

IP33 flush-fit junction box hollow walls 134x204x61



Features

Application:	Domestic
Apto para instalación en exterior:	No
Type of installation:	Flush-fit hollow walls
Calidad del material:	Polystyrene (PS)

Modular capacity

Technical data

Glow wire resistance (°C):	850
----------------------------	-----

Dimensions

Piece dimensions Height x Width x Depth (mm):	153 x 223 x 64
hueco_empotrar_alto_ancho_profundo_mm:	134 x 204 x 61

Additional features

Door/window/lid type:	Opaca atornillada
Sujeción de puerta/tapa/ventana:	Screw-on
Reversible door:	No
UV protection:	No
No. of doors:	1
Lock type:	Con tornillos

Tipo de cubierta:	Cover
Versión de la cubierta:	Blind cover
Sealable:	No
Enlazable:	No
Neutral and earth bars:	No
Incorpora Raíl DIN:	No
Plate:	No
Placa ajustable:	No
Placa perforada:	No

Materials

Materiales libres de halógenos:	Yes
Base material:	ABS
Door/window/lid material:	Polystyrene (PS)
Color:	WhiteRAL 9003
Base colour:	WhiteRAL 9003

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)

20	25	30	35	40
4.3	5.3	6.4	7.4	8.5

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 38

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.153 x 0.223 x 0.064

Package weight (kg): 0.248

Peso bruto unitario (kg): 0.273

Codes

EAN code GETIM13: 8431044529912

Tariff code: 85381000

ETIM 8.0 Code: EC002601

Código ETIM 9.0: EC002601

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Downloads (links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/CT1522PH.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/CT1522PH.dxf>

Product drawing (PDF):

<https://ide.es/docs/planos/pdf/CT1522PH.pdf>

Assembly instructions:

91452