

Serie Domos-K wiring

Mechanism boxes for hollow walls

Reference : D70/4K

Mechanism box 4 crowns for hollow walls with screws



Features

Application:	Domestic
Apto para instalación en exterior:	No
Type of installation:	Flush-fit hollow walls
Calidad del material:	Self-extinguishing polypropylene (PP+TPE)

Modular capacity

Technical data

Glow wire resistance (°C):	850
Ball pressure test (°C):	70

Dimensions

Crown (mm):	68
Piece dimensions Height x Width x Depth (mm):	284 x 70.5 x 48
hueco_empotrar_alto_ancho_profundo_mm:	280.5 x 68 x 48
Cable entry - WidthxDepth (mm):	4xØ4-10/4xØ4-20/4xØ10-20/4xØ10-25

Additional features

Door/window/lid type:	Sin tapa
Reversible door:	No
UV protection:	No

Sealable:	No
Enlazable:	Yes
Neutral and earth bars:	No
Incorpora Raíl DIN:	No
Plate:	No
Placa ajustable:	No
Placa perforada:	No

Materials

Materiales libres de halógenos:	No
Color:	Blue

Electrical properties

Maximum voltage (V): 400

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)

20	25	30	35	40
3.3	4.1	4.9	5.7	6.5

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 60670-1-22

Packaging

Type d'emballage: NE

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 45

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.071 x 0.284 x 0.049

Package weight (kg): 0.153

Peso bruto unitario (kg): 0.168

Codes

EAN code GETIM13: 8431044159041

Tariff code: 85381000

ETIM 8.0 Code: EC002601

Código ETIM 9.0: EC002601

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/D704K.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/D704K.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/D704K.pdf>