

Serie -

-

Reference : DFF54PH/RTR50608PLAS



Features

Application:	Construction
Apto para instalación en exterior:	No
Type of installation:	Flush-fit hollow walls
Calidad del material:	Polystyrene (PS)

Modular capacity

Capacity/Number of modules:	3x18 (54)
Number of rows:	3

Technical data

Protection degree:	IP33
Box impact resistance:	IK08
RTR resistance to impact:	IK07
Glow wire resistance (°C):	850
Ball pressure test (°C):	70
Double insulation:	Class II

Dimensions

DFF box outer dimensions HeightxWidthxDepth (mm):	532x408x105
DFF flush-fit gap HeightxWidthxDepth (mm):	497x376x72

RTR box outer dimensions HeightxWidthxDepth (mm): 532x668x105

RTR flush-fit gap Alt.xAnch.Prof. (mm): 500x641x72

Additional features

Door/window/lid type:	Opaca
Sujeción de puerta/tapa/ventana:	Snap-fit
Reversible door:	Yes
UV protection:	No
No. of doors:	2
Lock type:	Puerta a presión
Tipo de cubierta:	Door
Versión de la cubierta:	Notched
Sealable:	No
Enlazable:	Yes
Neutral and earth bars:	No
Incorpora Raíl DIN:	Yes
Plate:	No
Placa ajustable:	No
Placa perforada:	No

Materials

Materiales libres de halógenos:	Yes
Base material:	ABS
Frame material:	Polystyrene (PS)
Door/window/lid material:	Polystyrene (PS)
Base colour:	Grey RAL 7035
Frame color:	WhiteRAL 9003
Door color:	WhiteRAL 9003

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)

20	25	30	35	40
61.0	76.2	91.5	106.7	122.0

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.54 x 0.337 x 0.118

Package weight (kg): 6.894

Peso bruto unitario (kg): 7.583

Codes

EAN code GETIM13: 8431044371290

Tariff code: 85381000

ETIM 8.0 Code: EC002601

Código ETIM 9.0: EC002601

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/DFF54PHRTR50608PLAS.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/DFF54PHRTR50608PLAS.pdf>

Assembly instructions: 91088