

# Serie Tecno Inox

IP66 Stainless steel terminal boxes

**Reference : ELA201590/INX**

IP66 AISI 304L stainless steel terminal box 200x150x90 plain sides screw-on lid



## Features

|                                               |                                      |
|-----------------------------------------------|--------------------------------------|
| Application:                                  | Corrosive environments,Food industry |
| Apto para instalación en exterior:            | No                                   |
| Type of installation:                         | Surface                              |
| Piece dimensions Height x Width x Depth (mm): | 200 x 150 x 90                       |
| Calidad del material:                         | AISI 304 stainless steel             |

## Technical data

|                            |              |
|----------------------------|--------------|
| Protection degree:         | IP66         |
| NEMA degree of protection: | 1, 4, 4x, 12 |
| Resistance to impact:      | IK10         |

## Dimensions

|                                               |                |
|-----------------------------------------------|----------------|
| Piece dimensions Height x Width x Depth (mm): | 200 x 150 x 90 |
| espacio_apertura_boca_cuerpo_alto_ancho_mm:   | 175 x 125      |

## Additional features

|                                  |                   |
|----------------------------------|-------------------|
| Door/window/lid type:            | Opaca atornillada |
| Sujeción de puerta/tapa/ventana: | Screw-on          |
| Reversible door:                 | No                |
| Body type:                       | Compact           |
| Lock type:                       | Con tornillos     |
| Plate:                           | No                |
| Placa ajustable:                 | No                |
| Placa perforada:                 | No                |
| Modelo mural apoyado:            | No                |
| Módulo en esquina:               | No                |
| Montaje intermedio:              | No                |
| Tejadillo inclinado:             | No                |

## Materials

|                                  |                              |
|----------------------------------|------------------------------|
| Lock material:                   | Cierre TECNO INOX-ATEX       |
| Seal material:                   | Polyurethane                 |
| Acabado:                         | Satin finish with Scotch 320 |
| Body thickness (mm):             | 1.2                          |
| Top/bottom panel thickness (mm): | 1.2                          |

## Maximum loads

---

## Electrical properties

---

**Maximum voltage (V):** 1000 AC / 1500 DC

**Power dissipation:**

| Power dissipation P(W) as a function of temperature increase ?T (°C) |      |      |      |      |
|----------------------------------------------------------------------|------|------|------|------|
| 20                                                                   | 25   | 30   | 35   | 40   |
| 10.3                                                                 | 12.8 | 15.4 | 18.0 | 20.5 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

---

## Certificates and regulations

---

**Directive:** 2014/35/EU

**Norms:** UNE-EN 62208

---

## Packaging

---

**Type d'emballage:** BX

**U.M. Embalaje - Unitario:** C62

**Minimum amount of sale:** 1

**dimensiones\_embalaje\_unitario\_alto\_ancho\_prof\_m:** 0.22 x 0.165 x 0.11

**Package weight (kg):** 1.497

**Peso bruto unitario (kg):** 1.647

---

## Codes

|                   |               |
|-------------------|---------------|
| EAN code GETIM13: | 8431044225487 |
| Tariff code:      | 85381000      |
| ETIM 8.0 Code:    | EC002713      |
| Código ETIM 9.0:  | EC002713      |

## Environmental

|                                             |                           |
|---------------------------------------------|---------------------------|
| Fecha verificación sustancias SVHC (reach): | 0000-00-00 00:00:00       |
| Packaging:                                  | 100% recyclable cardboard |

## Downloads (links)

|                            |                                                                                                               |
|----------------------------|---------------------------------------------------------------------------------------------------------------|
| Product drawing STP (URL): | <a href="https://ide.es/docs/planos/stp/ELA201590INX.stp">https://ide.es/docs/planos/stp/ELA201590INX.stp</a> |
| Product drawing DXF (URL): | <a href="https://ide.es/docs/planos/dxf/ELA201590INX.dxf">https://ide.es/docs/planos/dxf/ELA201590INX.dxf</a> |
| Product drawing (PDF):     | <a href="https://ide.es/docs/planos/pdf/ELA201590INX.pdf">https://ide.es/docs/planos/pdf/ELA201590INX.pdf</a> |