

# Serie Argenta Plus ENL

IP55 Rolled steel floor-standing combinable cabinets

**Reference : ENL2008040PT/SP**

IP55 Combinable floor-standing cabinet 2000x800x400  
transparent door without plate



## Features

|                                               |                            |
|-----------------------------------------------|----------------------------|
| Application:                                  | Large engineering projects |
| Apto para instalación en exterior:            | No                         |
| Type of installation:                         | Floor-standing             |
| Piece dimensions Height x Width x Depth (mm): | 2000 x 800 x 400           |
| Calidad del material:                         | Rolled steel               |

## Technical data

|                            |       |
|----------------------------|-------|
| Protection degree:         | IP55  |
| NEMA degree of protection: | 1, 12 |
| Resistance to impact:      | IK09  |

## Dimensions

|                                                          |                  |
|----------------------------------------------------------|------------------|
| Piece dimensions Height x Width x Depth (mm):            | 2000 x 800 x 400 |
| Cable entry - WidthxDepth (mm):                          | 570x310          |
| Usable inner space - Height (mm):                        | 1910 x 710 x 310 |
| Glass door with transparent panel - Height x Width (mm): | 1786 x 630       |

## Additional features

|                          |                                           |
|--------------------------|-------------------------------------------|
| Door/window/lid type:    | Transparente única                        |
| Reversible door:         | Yes                                       |
| No. of doors:            | 1                                         |
| Body type:               | Combinable                                |
| Lock type:               | Maneta de palanca + inserto doble barra 5 |
| Plate:                   | No                                        |
| Placa ajustable:         | No                                        |
| Placa perforada:         | No                                        |
| No. of hinges:           | 4                                         |
| No. locks:               | 1                                         |
| Closure - No. of points: | 4 points                                  |
| Cierre - Tipo llave:     | 5 mm double-bit Zamak key included        |
| Modelo mural apoyado:    | Yes                                       |
| Módulo en esquina:       | No                                        |
| Montaje intermedio:      | No                                        |
| Tejadillo inclinado:     | No                                        |
| Additional Information:  | Polyamide GF handle RAL 7016              |

## Materials

|                                  |                                   |
|----------------------------------|-----------------------------------|
| Door/window/lid material:        | Tempered glass                    |
| Lock material:                   | Poliamida 6 + GF30                |
| Seal material:                   | Polyurethane                      |
| Color:                           | Grey RAL 7035                     |
| Acabado:                         | Embossed hardened polyester paint |
| Door thickness (mm):             | 4                                 |
| Top/bottom panel thickness (mm): | 1.5                               |
| Rear panel thickness (mm):       | 1.5                               |
| Cable entry lid thickness (mm):  | 1.2                               |

## Maximum loads

## Electrical properties

**Maximum voltage (V):** 1000 AC / 1500 DC

**Intensidad nominal (A):** Up to 6200 (depending on type of accessory).

**Power dissipation:**

Power dissipation P(W) as a function of temperature increase  $\Delta T$  (°C)

| 20    | 25    | 30    | 35    | 40    |
|-------|-------|-------|-------|-------|
| 454.1 | 567.6 | 681.1 | 794.6 | 908.2 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

## Certificates and regulations

**Directive:** 2014/35/EU

**Norms:** UNE-EN 62208, UNE-EN 61439-1

## Packaging

**Type d'emballage:** PF

**U.M. Embalaje - Unitario:** C62

**Minimum amount of sale:** 1

**dimensiones\_embalaje\_unitario\_alto\_ancho\_prof\_m:** 2.175 x 0.85 x 0.55

**Package weight (kg):** 90.231

**Peso bruto unitario (kg):** 99.254

## Codes

|                          |               |
|--------------------------|---------------|
| <b>EAN code GETIM13:</b> | 8431044117164 |
| <b>Tariff code:</b>      | 85381000      |
| <b>ETIM 8.0 Code:</b>    | EC000261      |
| <b>Código ETIM 9.0:</b>  | EC000261      |

## Environmental

|                                                    |                           |
|----------------------------------------------------|---------------------------|
| <b>Fecha verificación sustancias SVHC (reach):</b> | 0000-00-00 00:00:00       |
| <b>Packaging:</b>                                  | 100% recyclable cardboard |

## Downloads (links)

|                               |                               |
|-------------------------------|-------------------------------|
| <b>Assembly instructions:</b> | 92871                         |
| <b>Videos:</b>                | ARGENTA PLUS PO ENL (ESP-ING) |