

# Serie -

-

Reference : GME70PH/RTR50608PME



## Features

|                                    |                        |
|------------------------------------|------------------------|
| Application:                       | Construction           |
| Apto para instalación en exterior: | No                     |
| Type of installation:              | Flush-fit hollow walls |

## Modular capacity

|                             |           |
|-----------------------------|-----------|
| Capacity/Number of modules: | 5x14 (70) |
| Number of rows:             | 5         |

## Technical data

|                            |          |
|----------------------------|----------|
| Protection degree:         | IP33     |
| Box impact resistance:     | IK08     |
| RTR resistance to impact:  | IK07     |
| Glow wire resistance (°C): | 850      |
| Double insulation:         | Class II |

## Dimensions

|                                                   |            |
|---------------------------------------------------|------------|
| GME box outer dimensions HeightxWidthxDepth (mm): | 877x387x97 |
| GME flush-fit gap HeightxWidthxDepth (mm):        | 844x354x87 |
| RTR box outer dimensions HeightxWidthxDepth (mm): | 627x775x99 |
| RTR flush-fit gap Alt.xAnch.Prof. (mm):           | 592x740x89 |

## Additional features

|                         |                  |
|-------------------------|------------------|
| Door/window/lid type:   | Opaca            |
| Reversible door:        | Yes              |
| UV protection:          | No               |
| No. of doors:           | 2                |
| Lock type:              | Cierre a presión |
| No. locks:              | 3                |
| Tipo de cubierta:       | Door             |
| Versión de la cubierta: | Closed           |
| Sealable:               | No               |
| Enlazable:              | Yes              |
| Neutral and earth bars: | No               |
| Incorpora Raíl DIN:     | Yes              |
| Plate:                  | No               |
| Placa ajustable:        | No               |
| Placa perforada:        | No               |

## Materials

|                                 |                  |
|---------------------------------|------------------|
| Materiales libres de halógenos: | Yes              |
| Base material:                  | ABS              |
| Frame material:                 | Rolled steel     |
| Door/window/lid material:       | Rolled steel     |
| Chassis lid material:           | Polystyrene (PS) |
| Lock material:                  | ABS              |
| Base colour:                    | Grey RAL 7035    |
| Frame color:                    | WhiteRAL 9003    |
| Door color:                     | WhiteRAL 9003    |
| Acabado:                        | Liso             |

## Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)

| 20        | 25        | 30        | 35        | 40        |
|-----------|-----------|-----------|-----------|-----------|
| 36.6/35.6 | 45.7/44.5 | 54.9/53.4 | 64.0/62.3 | 73.2/71.2 |

## Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

## Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones\_embalaje\_unitario\_alto\_ancho\_prof\_m: 0.644 x 0.399 x 0.113

Package weight (kg): 13.705

Peso bruto unitario (kg): 15.076

## Codes

EAN code GETIM13: 8431044479187

Tariff code: 85381000

ETIM 8.0 Code: EC002601

Código ETIM 9.0: EC002601

## Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

## Downloads (links)

Assembly instructions:

91098