

Serie -

-

Reference : GME70/RTR50608PME



Features

Application:	Construction
Apto para instalación en exterior:	No
Type of installation:	Flush-fit brick walls

Modular capacity

Capacity/Number of modules:	5x14 (70)
Number of rows:	5

Technical data

Protection degree:	IP33
Box impact resistance:	IK08
RTR resistance to impact:	IK07
Glow wire resistance (°C):	650
Double insulation:	Class II

Dimensions

GME box outer dimensions HeightxWidthxDepth (mm):	877x387x99
GME flush-fit gap HeightxWidthxDepth (mm):	842x352x89
RTR box outer dimensions HeightxWidthxDepth (mm):	627x775x99
RTR flush-fit gap Alt.xAnch.Prof. (mm):	592x740x89

Additional features

Door/window/lid type:	Opaca
Reversible door:	Yes
UV protection:	No
No. of doors:	2
Lock type:	Cierre a presión
No. locks:	3
Tipo de cubierta:	Door
Versión de la cubierta:	Closed
Sealable:	No
Enlazable:	Yes
Neutral and earth bars:	No
Incorpora Raíl DIN:	Yes
Plate:	No
Placa ajustable:	No
Placa perforada:	No

Materials

Materiales libres de halógenos:	Yes
Base material:	Polystyrene (PS)
Frame material:	Rolled steel
Door/window/lid material:	Rolled steel
Chassis lid material:	Polystyrene (PS)
Lock material:	ABS
Base colour:	Grey RAL 7035
Frame color:	WhiteRAL 9003
Door color:	WhiteRAL 9003
Acabado:	Liso

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)

20	25	30	35	40
36.6/35.6	45.7/44.5	54.9/53.4	64.0/62.3	73.2/71.2

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.644 x 0.399 x 0.113

Package weight (kg): 13.225

Peso bruto unitario (kg): 14.547

Codes

EAN code GETIM13: 8431044479149

Tariff code: 85381000

ETIM 8.0 Code: EC002601

Código ETIM 9.0: EC002601

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Assembly instructions:

91098