

Serie Gold-MM Multimedia

IP40 Flush-fit with metal door multimedia boxes

Reference : GMEM56PO

IP40 Multimedia boxes. Flush-fit enclosure with multimedia plate
425x295 +14 modules



Features

Application:	Tertiary (residential)
Apto para instalación en exterior:	No
Type of installation:	Flush-fit brick walls
Calidad del material:	Rolled steel

Modular capacity

Capacity/Number of modules:	1x14
Number of rows:	1

Technical data

Protection degree:	IP40
Resistance to impact:	IK08
Glow wire resistance (°C):	650
Double insulation:	Class II

Dimensions

Piece dimensions Height x Width x Depth (mm):	752 x 387 x 99
hueco_empotrar_alto_ancho_profundo_mm:	717 x 352 x 89
Rear cable entry (mm):	2x[2xM25-1xM32-1xM40]
Left cable entry (mm):	6xø50-1x(80x54)
Dim. placa - Alto (mm); Dim. placa - Ancho (mm):	425 x 295

Additional features

Door/window/lid type:	Opaca
Reversible door:	No
UV protection:	No
No. of doors:	1
Lock type:	Cierre a presión
No. locks:	1
Cierre - Tipo llave:	Without key Possibility of lock with key as accessory (ref. 22040)
Tipo de cubierta:	Door
Versión de la cubierta:	Closed
Sealable:	No
Enlazable:	Yes
Neutral and earth bars:	No
Incorpora Raíl DIN:	Yes
Plate:	Yes
Plate type:	Micro-perforated
Placa ajustable:	No
Placa perforada:	Yes

Materials

Materiales libres de halógenos:	Yes
Base material:	Polystyrene (PS)
Frame material:	Rolled steel
Door/window/lid material:	Rolled steel
Chassis lid material:	Polystyrene (PS)
Lock material:	ABS
Base colour:	Grey RAL 7035
Frame color:	WhiteRAL 9003
Door color:	WhiteRAL 9003
Acabado:	Liso

Electrical properties

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)				
20	25	30	35	40
31.4	39.3	47.1	55.0	62.8

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Packaging

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	2
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.769 x 0.399 x 0.113
Package weight (kg):	5.357
Peso bruto unitario (kg):	5.893

Codes

EAN code GETIM13:	8431044535715
Tariff code:	85381000
ETIM 8.0 Code:	EC000214
Código ETIM 9.0:	EC000214

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
---	---------------------

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/GMEM56PO.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/GMEM56PO.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/GMEM56PO.pdf

Assembly instructions:

Assembly Instructions: Gold Metal Flush-Fit Multimedia 42-56-70