

Serie Gold-MM Multimedia

IP40 Flush-fit with metal door multimedia boxes

Reference : GMEM70PO28/RR

IP40 Multimedia boxes. Flush-fit enclosure with multimedia plate 550x295 + 28 modules. With neutral and earth bars



Features

Application:	Tertiary (residential)
Apto para instalación en exterior:	No
Type of installation:	Flush-fit brick walls
Calidad del material:	Rolled steel

Modular capacity

Capacity/Number of modules:	2x14 (28)
Number of rows:	2

Technical data

Protection degree:	IP40
Resistance to impact:	IK08
Glow wire resistance (°C):	650
Double insulation:	Class II

Dimensions

Piece dimensions Height x Width x Depth (mm):	502 x 387 x 99
hueco_empotrar_alto_ancho_profundo_mm:	842 x 352 x 89
Rear cable entry (mm):	2x[2xM25-1xM32-1xM40]
Left cable entry (mm):	8xø50-1x(80x54)
Dim. placa - Alto (mm); Dim. placa - Ancho (mm):	550 x 295

Additional features

Door/window/lid type:	Opaca
Reversible door:	No
UV protection:	No
No. of doors:	1
Lock type:	Cierre a presión
No. locks:	1
Cierre - Tipo llave:	Without key Possibility of lock with key as accessory (ref. 22040)
Tipo de cubierta:	Door
Versión de la cubierta:	Closed
Sealable:	No
Enlazable:	Yes
Neutral and earth bars:	Yes
Neutral and ground cable section (mm²):	8x(2,5-6)+8x(4-10)+1x(10-25)+1x(16-35)
Incorpora Raíl DIN:	Yes
Plate:	Yes
Plate type:	Micro-perforated
Placa ajustable:	No
Placa perforada:	Yes

Materials

Materiales libres de halógenos:	Yes
Base material:	Polystyrene (PS)
Frame material:	Rolled steel
Door/window/lid material:	Rolled steel
Chassis lid material:	Polystyrene (PS)
Lock material:	ABS
Base colour:	Grey RAL 7035
Frame color:	WhiteRAL 9003
Door color:	WhiteRAL 9003
Acabado:	Liso

Electrical properties

Max. Current (A): 125

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)

20	25	30	35	40
36.6	45.7	54.9	64.0	73.2

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 2

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.894 x 0.399 x 0.108

Package weight (kg): 6.96

Peso bruto unitario (kg): 7.656

Codes

EAN code GETIM13: 8431044115689

Tariff code: 85381000

ETIM 8.0 Code: EC000214

Código ETIM 9.0: EC000214

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Downloads (links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/GMEM70PO28RR.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/GMEM70PO28RR.dxf>

Product drawing (PDF):

<https://ide.es/docs/planos/pdf/GMEM70PO28RR.pdf>

Assembly instructions:

Assembly Instructions: Gold Metal Flush-Fit Multimedia 42-56-70 RR/RA