

Serie Argenta

IP66 Rolled steel wall-mounting cabinets

Reference : GN12012025/SP

IP66 Rolled steel wall-mounting cabinet 1200x1200x250 without mounting plate



Features

Application:	Automation and control
Apto para instalación en exterior:	No
Type of installation:	Wall-mounting
Piece dimensions Height x Width x Depth (mm):	1200 x 1200 x 250
Calidad del material:	Rolled steel

Technical data

Protection degree:	IP66
NEMA degree of protection:	1, 4, 12
Resistance to impact:	IK10

Dimensions

Piece dimensions Height x Width x Depth (mm):	1200 x 1200 x 250
Wall-mounting Height x Width (mm):	1160 x 1160
Cable entry - WidthxDepth (mm):	2x(125x485)
Usable inner space - Height (mm):	1150 x 1150 x 229
Glass door with transparent panel - Height x Width (mm):	1097 x 1019

Additional features

Door/window/lid type:	Opaca única
Reversible door:	Yes
No. of doors:	1
Body type:	Compact
Lock type:	Doble barra 5
Plate:	No
Placa ajustable:	No
Placa perforada:	No
No. of hinges:	3
No. locks:	1
Closure - No. of points:	3 points
Cierre - Tipo llave:	5 mm double-bit Polyamide key included
No. of door profiles:	4
Modelo mural apoyado:	No
Módulo en esquina:	No
Montaje intermedio:	No
Tejadillo inclinado:	No

Materials

Lock material:	Poliamida
Seal material:	Polyurethane
Color:	Grey RAL 7035
Acabado:	Embossed hardened polyester paint
Body thickness (mm):	1.5
Door thickness (mm):	1.5
Cable entry lid thickness (mm):	2

Maximum loads

Total maximum load (kg): 390

Maximum door load (kg): 40

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)				
20	25	30	35	40
327.4	409.2	491.0	572.9	654.7

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 1.21 x 1.205 x 0.27

Package weight (kg): 58.847

Peso bruto unitario (kg): 64.731

Codes

EAN code GETIM13:	8431044021805
Tariff code:	85381000
ETIM 8.0 Code:	EC000261
Código ETIM 9.0:	EC000261

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/GN12012025SP.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/GN12012025SP.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/GN12012025SP.pdf
Assembly instructions:	92890