

Serie Argenta

IP66 Rolled steel wall-mounting cabinets

Reference : GNT403020

IP66 Rolled steel wall-mounting cabinet 400x300x200
transparent door with mounting plate



Features

Application:	Automation and control
Apto para instalación en exterior:	No
Type of installation:	Wall-mounting
Piece dimensions Height x Width x Depth (mm):	400 x 300 x 200
Calidad del material:	Rolled steel

Technical data

Protection degree:	IP66
NEMA degree of protection:	1, 4, 12
Resistance to impact:	IK08

Dimensions

Piece dimensions Height x Width x Depth (mm):	400 x 300 x 200
Wall-mounting Height x Width (mm):	360 x 260
Dim. placa - Alto (mm); Dim. placa - Ancho (mm):	370 x 250
Cable entry - WidthxDepth (mm):	125x215
Usable inner space - Height (mm):	350 x 250 x 179
Glass door with transparent panel - Height x Width (mm):	296 x 148

Additional features

Door/window/lid type:	Transparente única
Reversible door:	Yes
No. of doors:	1
Body type:	Compact
Lock type:	Doble barra 5
Plate:	Yes
Plate type:	Plain
Placa ajustable:	No
Placa perforada:	No
No. of hinges:	2
No. locks:	1
Closure - No. of points:	1 point
Cierre - Tipo llave:	5 mm double-bit Polyamide key included
No. of door profiles:	2
Modelo mural apoyado:	No
Módulo en esquina:	No
Montaje intermedio:	No
Tejadillo inclinado:	No

Materials

Door/window/lid material:	Tempered glass
Lock material:	Poliamida
Plate material:	Galvanised steel
Seal material:	Polyurethane
Color:	Grey RAL 7035
Acabado:	Embossed hardened polyester paint
Body thickness (mm):	1.2
Door thickness (mm):	4
Plate thickness (mm):	2
Cable entry lid thickness (mm):	2



Maximum loads

Total maximum load (kg):	175
Maximum door load (kg):	25
Maximum plate load (kg):	150

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC
----------------------	-------------------

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)

20	25	30	35	40
43.5	54.4	65.3	76.2	87.1

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 62208, UNE-EN 61439-1

Packaging

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.42 x 0.315 x 0.22
Package weight (kg):	8.17
Peso bruto unitario (kg):	8.987

Codes

EAN code GETIM13:	8431044455068
Tariff code:	85381000
ETIM 8.0 Code:	EC000261
Código ETIM 9.0:	EC000261

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/GNT403020.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/GNT403020.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/GNT403020.pdf
Assembly instructions:	92890