

# Serie Gold-P flush-fit

IP40 Flush-fit plastic distribution boxes

**Reference : GPE12PT/PH/RR**

IP40 Flush-fit hollow walls distribution box 1x12 modules  
transparent door PE+N



## Features

|                                    |                        |
|------------------------------------|------------------------|
| Application:                       | Tertiary (residential) |
| Apto para instalación en exterior: | No                     |
| Type of installation:              | Flush-fit hollow walls |

## Modular capacity

|                             |      |
|-----------------------------|------|
| Capacity/Number of modules: | 1x12 |
| Number of rows:             | 1    |

## Technical data

|                            |          |
|----------------------------|----------|
| Protection degree:         | IP40     |
| Resistance to impact:      | IK08     |
| Glow wire resistance (°C): | 850      |
| Ball pressure test (°C):   | 70       |
| Double insulation:         | Class II |

## Dimensions

|                                               |                               |
|-----------------------------------------------|-------------------------------|
| Piece dimensions Height x Width x Depth (mm): | 284 x 316 x 97                |
| hueco_empotrar_alto_ancho_profundo_mm:        | 256 x 288 x 72                |
| Upper cable entry (mm):                       | 4x4                           |
| Bottom cable entry (mm):                      | 1xM50/M40 4xM25/M20 5xM25/M16 |
| Rear cable entry (mm):                        | 2xM40/M32 4xM25               |

---

|                        |       |
|------------------------|-------|
| Left cable entry (mm): | 2xØ32 |
|------------------------|-------|

---

## Additional features

---

|                                         |                                                                    |
|-----------------------------------------|--------------------------------------------------------------------|
| Door/window/lid type:                   | Transparente                                                       |
| Reversible door:                        | Yes                                                                |
| UV protection:                          | No                                                                 |
| No. of doors:                           | 1                                                                  |
| Lock type:                              | Cierre a presión                                                   |
| No. locks:                              | 1                                                                  |
| Cierre - Tipo llave:                    | Without key Possibility of lock with key as accessory (ref. 22015) |
| Tipo de cubierta:                       | Door                                                               |
| Versión de la cubierta:                 | Closed                                                             |
| Sealable:                               | No                                                                 |
| Enlazable:                              | Yes                                                                |
| Neutral and earth bars:                 | Yes                                                                |
| Neutral and ground cable section (mm²): | 6x(2,5-6)+6x(4-10)+1x(10-25)+1x(16-35)                             |
| Incorpora Raíl DIN:                     | Yes                                                                |
| Plate:                                  | No                                                                 |
| Placa ajustable:                        | No                                                                 |
| Placa perforada:                        | No                                                                 |

---

## Materials

---

|                                 |                    |
|---------------------------------|--------------------|
| Materiales libres de halógenos: | Yes                |
| Base material:                  | ABS                |
| Frame material:                 | ABS                |
| Door/window/lid material:       | Polycarbonate (PC) |
| Chassis lid material:           | ABS                |
| Base colour:                    | Grey RAL 7035      |
| Frame color:                    | WhiteRAL 9003      |
| Door color:                     | Tinted             |

---

## Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Max. Current (A): 125

Power dissipation:

Power dissipation P(W) as a function of temperature increase  $\Delta T$  (°C)

| 20   | 25   | 30   | 35   | 40   |
|------|------|------|------|------|
| 12.2 | 15.3 | 18.4 | 21.4 | 24.5 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

## Certificates and regulations

Directive: 2014/35/EU

Norms: EN-IEC 62208:2023, EN-IEC 60670-1:2021/A11:2021; EN 60670-24:2013/A11:2023

## Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 8

dimensiones\_embalaje\_unitario\_alto\_ancho\_prof\_m: 0.295 x 0.321 x 0.108

Package weight (kg): 1.376

Peso bruto unitario (kg): 1.513

## Codes

EAN code GETIM13: 8431044188393

Tariff code: 85381000

ETIM 8.0 Code: EC000214

Código ETIM 9.0: EC000214

## Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

## Downloads (links)

---

|                            |                                                                                                             |
|----------------------------|-------------------------------------------------------------------------------------------------------------|
| Product drawing STP (URL): | <a href="https://ide.es/docs/planos/stp/GPE12PTPHRR.stp">https://ide.es/docs/planos/stp/GPE12PTPHRR.stp</a> |
| Product drawing DXF (URL): | <a href="https://ide.es/docs/planos/dxf/GPE12PTPHRR.dxf">https://ide.es/docs/planos/dxf/GPE12PTPHRR.dxf</a> |
| Product drawing (PDF):     | <a href="https://ide.es/docs/planos/pdf/GPE12PTPHRR.pdf">https://ide.es/docs/planos/pdf/GPE12PTPHRR.pdf</a> |
| Assembly instructions:     | 91377                                                                                                       |
| Videos:                    | GOLD-P EMPOTRAR Y SUPERFICIE LOW                                                                            |