

# Serie Light

IP65-IP67 Junction boxes

**Reference : GSX322**

IP65 - IP67 Motor-protection box knock-out entries  
243x333x191



## Features

|                                    |                                                     |
|------------------------------------|-----------------------------------------------------|
| Application:                       | Industrial (Watertight and distribution enclosures) |
| Apto para instalación en exterior: | Yes                                                 |
| Type of installation:              | Surface                                             |
| Calidad del material:              | Polystyrene (PS)                                    |

## Modular capacity

## Technical data

|                            |           |
|----------------------------|-----------|
| Protection degree:         | IP65-IP67 |
| Resistance to impact:      | IK07      |
| Glow wire resistance (°C): | 650       |
| Ball pressure test (°C):   | 70        |
| Double insulation:         | Class II  |

## Dimensions

|                                               |                 |
|-----------------------------------------------|-----------------|
| Piece dimensions Height x Width x Depth (mm): | 243 x 333 x 191 |
| Cable entry No. conical glands M40:           | 12              |

## Additional features

|                                  |            |
|----------------------------------|------------|
| Door/window/lid type:            | Opaca alta |
| Sujeción de puerta/tapa/ventana: | Screw-on   |

---

|                         |               |
|-------------------------|---------------|
| Reversible door:        | No            |
| UV protection:          | No            |
| No. of doors:           | 1             |
| Lock type:              | Con tornillos |
| Tipo de cubierta:       | Cover         |
| Versión de la cubierta: | Blind cover   |
| Sealable:               | Yes           |
| Enlazable:              | No            |
| Neutral and earth bars: | No            |
| Incorpora Raíl DIN:     | No            |
| Plate:                  | No            |
| Placa ajustable:        | No            |
| Placa perforada:        | No            |

---

## Materials

---

|                                 |                  |
|---------------------------------|------------------|
| Materiales libres de halógenos: | Yes              |
| Base material:                  | Polystyrene (PS) |
| Door/window/lid material:       | Polystyrene (PS) |
| Cone material:                  | PVC              |
| Base colour:                    | Grey RAL 7035    |
| Cone color:                     | Grey RAL 7035    |

---

## Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase  $\Delta T$  (°C)

| 20   | 25   | 30   | 35   | 40   |
|------|------|------|------|------|
| 19.4 | 24.2 | 29.1 | 33.9 | 38.8 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

## Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 60670-22

## Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 2

dimensiones\_embalaje\_unitario\_alto\_ancho\_prof\_m: 0.145 x 0.43 x 0.43

Package weight (kg): 1.314

Peso bruto unitario (kg): 1.445

## Codes

EAN code GETIM13: 8431044199702

Tariff code: 85381000

ETIM 8.0 Code: EC002600

Código ETIM 9.0: EC002600

## Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

## Downloads (links)

---

Product drawing STP (URL): <https://ide.es/docs/planos/stp/GSX322.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/GSX322.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/GSX322.pdf>