

Serie Regulating

Regulating

Reference : HG02

Hygrostat



Features

Apto para instalación en exterior: No

Additional features

Relative humidity range (%): 35-95
Electrical connection: 3-pole terminal
Device mounting: 35 mm DIN rail clip

Ventilation

Reversible: No

Heating

Regulating

Contact resistance (m ?): 10
Service life (cycles): > 50 000
Switching error (%RH): 4 (±3?% tolerance)
Allowed wind speed (m/s): 15
Min. Switching capacity (V): 20 AC/DC 100 mA
Max. Switching capacity (W): 20 DC
Max. Switching capacity (V): 250 AC 5 (1) A

Technical data

Protection degree:	IP20
--------------------	------

Materials

Calidad del material:	Plastic UL94 V0
-----------------------	-----------------

Filtro:	No
---------	----

Materiales libres de halógenos:	No
---------------------------------	----

Color:	Grey
--------	------

Dimensions

Piece dimensions Height x Width x Depth (mm):	67 x 50 x 38
---	--------------

Certificates and regulations

Directive:	2014/35/EU
------------	------------

Norms:	IEC 62208; IEC 61439-1
--------	------------------------

Packaging

Type d'emballage:	BX
-------------------	----

U.M. Embalaje - Unitario:	C62
---------------------------	-----

Minimum amount of sale:	1
-------------------------	---

dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.067 x 0.05 x 0.038
--	----------------------

Package weight (kg):	0.163
----------------------	-------

Peso bruto unitario (kg):	0.179
---------------------------	-------

Codes

EAN code GETIM13:	8431044251066
-------------------	---------------

Tariff code:	85369095
--------------	----------

ETIM 8.0 Code:	EC004587
----------------	----------

Código ETIM 9.0:	EC004587
------------------	----------

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (Links)

Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/HG02.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/HG02.pdf