

Serie Regulating

Regulating

Reference : HT250

Hygrotherm



Features

Apto para instalación en exterior: No

Additional features

Operating voltage (V): 230 AC 50/60 Hz

Relative humidity range (%): 50-90

Electrical connection: 5-pole terminal

Device mounting: 35 mm DIN rail clip

Ventilation

Reversible: No

Heating

Regulating

Setting range temperature (°C): 0-60

Contact resistance (m Ω): 10

Service life (cycles): NC: 50 000 / NA: 100 000

Max. Switching capacity (V): NC: 240 AC 6 (1) A NA: 240 AC 8 (1,6) A

Temperature switch difference: 2?K (±1?K tolerance) at 25?°C (50?%)

Humidity switch difference (%RH): 4?% RH (±1?% tolerance) at 25?°C (50?%)

Humidity reaction time (sec.): ?5

Optical indicator: LED

Technical data

Protection degree: IP20

Materials

Calidad del material: Plastic UL94 V0

Filtro: No

Materiales libres de halógenos: No

Color: Grey

Dimensions

Piece dimensions Height x Width x Depth (mm): 77 x 60 x 43

Certificates and regulations

Directive: 2014/35/EU

Norms: IEC 62208; IEC 61439-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.077 x 0.06 x 0.043

Package weight (kg): 0.162

Peso bruto unitario (kg): 0.178

Codes

EAN code GETIM13: 8431044400143

Tariff code: 85369095

ETIM 8.0 Code: EC004587

Código ETIM 9.0: EC004587

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (Links)

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/HT250.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/HT250.pdf>