

Serie Management systems: management systems

Management systems

Reference : IA3C2510

Automatic switch 3P 25AC 10KA 230/400V 50/60HZ compatible
with accessories



Features

Application:	Industrial
Tipo de producto:	Sistema de protección magnetotérmica
Curve:	C
Rated current - In (A):	25
Rated short-circuit breaking capacity (kA):	10
Piece dimensions Height x Width x Depth (mm):	87 x 54 x 78

Electrical specifications

Rated frequency (Hz):	50/60
Rated working voltage/Ue (V):	400
Rated insulated voltage/UI (V):	500
Maximum working voltage (V):	440
Dielectric test voltage (kV):	2
Mechanical durability (Cycles):	10000
Electrical durability (Cycles):	6000

Connection and installations

Ambient temperature (with daily average ? 35 °C) (°C):	-5 / +40
Reference temperature for setting of thermal element (°C):	30
Storage temperature (°C):	-25 / +70

Connection terminal protection degree:	IP40
Wire (mm ²):	25
Pollution degree:	2
Tightening torque (Nm):	3
Connection:	Top and bottom

Additional features

All sides protection degree:	IP20
Protección selectiva:	No
Desconexión de retardo:	No
Con dispositivo de cierre:	No
Equipos adicionales:	No
A prueba de explosiones:	No
Apto para instalación en exterior:	No

Materials

Materiales libres de halógenos:	No
---------------------------------	----

Certificates and regulations

Norms:	EN 60898-1
--------	------------

Packaging

Type d'emballage:	NE
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.087 x 0.054 x 0.078
Package weight (kg):	0.316
Peso bruto unitario (kg):	0.348

Codes

EAN code GETIM13:	8431044967073
Tariff code:	8536201090
ETIM 8.0 Code:	EC000042
Código ETIM 9.0:	EC000042

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)