

Serie Argenta Inox

IP66 Stainless steel wall-mounting cabinets

Reference : INX404020

IP66 Stainless steel 304L wall-mounting cabinet 400x400x200 with mounting plate



Features

Application:	Corrosive environments,Food industry
Apto para instalación en exterior:	No
Type of installation:	Wall-mounting
Piece dimensions Height x Width x Depth (mm):	400 x 400 x 200
Calidad del material:	AISI 304 stainless steel

Technical data

Protection degree:	IP66
NEMA degree of protection:	1, 4, 4x, 12
Resistance to impact:	IK10

Dimensions

Piece dimensions Height x Width x Depth (mm):	400 x 400 x 200
Wall-mounting Height x Width (mm):	360 x 360
Dim. placa - Alto (mm); Dim. placa - Ancho (mm):	370 x 350
Usable inner space - Height (mm):	350 x 350 x 179

Additional features

Door/window/lid type:	Opaca única
Reversible door:	Yes
No. of doors:	1
Body type:	Compact
Lock type:	Doble barra 5
Plate:	Yes
Plate type:	Plain
Placa ajustable:	No
Placa perforada:	No
No. of hinges:	2
No. locks:	1
Closure - No. of points:	1 point
Cierre - Tipo llave:	5 mm double-bit Zamak key included
No. of door profiles:	2
Modelo mural apoyado:	No
Módulo en esquina:	No
Montaje intermedio:	No
Tejadillo inclinado:	No

Materials

Lock material:	Zamak cromado
Plate material:	Galvanised steel
Seal material:	Polyurethane
Acabado:	Satin finish with Scotch 320
Body thickness (mm):	1.2
Door thickness (mm):	1.2
Plate thickness (mm):	2

Maximum loads

Total maximum load (kg):	225
Maximum door load (kg):	25
Maximum plate load (kg):	200

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC
----------------------	-------------------

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)				
20	25	30	35	40
52.8	66.0	79.2	92.4	105.6

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.42 x 0.415 x 0.22
Package weight (kg):	9.532
Peso bruto unitario (kg):	10.485

Codes

EAN code GETIM13:	8431044088600
Tariff code:	85381000
ETIM 8.0 Code:	EC000261
Código ETIM 9.0:	EC000261

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/INX404020.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/INX404020.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/INX404020.pdf
Assembly instructions:	92890_1