

Serie Argenta Inox

IP66 Stainless steel wall-mounting cabinets

Reference : INX705025-316

IP66 Stainless steel 316L wall-mounting cabinet 700x500x250 with mounting plate



Features

Application:	Corrosive environments,Food industry
Apto para instalación en exterior:	No
Type of installation:	Wall-mounting
Piece dimensions Height x Width x Depth (mm):	700 x 500 x 250
Calidad del material:	AISI 316 stainless steel

Technical data

Protection degree:	IP66
NEMA degree of protection:	1, 4, 4x, 12
Resistance to impact:	IK10

Dimensions

Piece dimensions Height x Width x Depth (mm):	700 x 500 x 250
Wall-mounting Height x Width (mm):	660 x 460
Dim. placa - Alto (mm); Dim. placa - Ancho (mm):	670 x 450
Usable inner space - Height (mm):	650 x 450 x 229

Additional features

Door/window/lid type:	Opaca única
Reversible door:	Yes
No. of doors:	1
Body type:	Compact
Lock type:	Doble barra 5
Plate:	Yes
Plate type:	Plain
Placa ajustable:	No
Placa perforada:	No
No. of hinges:	2
No. locks:	2
Closure - No. of points:	1 point
Cierre - Tipo llave:	5 mm double-bit Zamak key included
No. of door profiles:	2
Modelo mural apoyado:	No
Módulo en esquina:	No
Montaje intermedio:	No
Tejadillo inclinado:	No

Materials

Lock material:	Zamak cromado
Plate material:	Galvanised steel
Seal material:	Polyurethane
Acabado:	Satin finish with Scotch 320
Body thickness (mm):	1.5
Door thickness (mm):	1.5
Plate thickness (mm):	2

Maximum loads

Total maximum load (kg):	275
Maximum door load (kg):	25
Maximum plate load (kg):	250

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC
----------------------	-------------------

Power dissipation:

Power dissipation P(W) as a function of temperature increase ?T (°C)				
20	25	30	35	40
107.8	134.8	161.7	188.7	215.6

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.72 x 0.515 x 0.27
Package weight (kg):	22.14
Peso bruto unitario (kg):	24.354

Codes

EAN code GETIM13:	8431044088846
Tariff code:	85381000
ETIM 8.0 Code:	EC000261
Código ETIM 9.0:	EC000261

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/INX705025-316.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/INX705025-316.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/INX705025-316.pdf
Assembly instructions:	92890_1