

# Serie Argenta Inox

IP66 Stainless steel wall-mounting cabinets

**Reference : INX806025**

IP66 Stainless steel 304L wall-mounting cabinet 800x600x250 with mounting plate



## Features

|                                               |                                      |
|-----------------------------------------------|--------------------------------------|
| Application:                                  | Corrosive environments,Food industry |
| Apto para instalación en exterior:            | No                                   |
| Type of installation:                         | Wall-mounting                        |
| Piece dimensions Height x Width x Depth (mm): | 800 x 600 x 250                      |
| Calidad del material:                         | AISI 304 stainless steel             |

## Technical data

|                            |              |
|----------------------------|--------------|
| Protection degree:         | IP66         |
| NEMA degree of protection: | 1, 4, 4x, 12 |
| Resistance to impact:      | IK10         |

## Dimensions

|                                                  |                 |
|--------------------------------------------------|-----------------|
| Piece dimensions Height x Width x Depth (mm):    | 800 x 600 x 250 |
| Wall-mounting Height x Width (mm):               | 760 x 560       |
| Dim. placa - Alto (mm); Dim. placa - Ancho (mm): | 770 x 550       |
| Usable inner space - Height (mm):                | 750 x 550 x 229 |

## Additional features

|                          |                                    |
|--------------------------|------------------------------------|
| Door/window/lid type:    | Opaca única                        |
| Reversible door:         | Yes                                |
| No. of doors:            | 1                                  |
| Body type:               | Compact                            |
| Lock type:               | Doble barra 5                      |
| Plate:                   | Yes                                |
| Plate type:              | Plain                              |
| Placa ajustable:         | No                                 |
| Placa perforada:         | No                                 |
| No. of hinges:           | 3                                  |
| No. locks:               | 2                                  |
| Closure - No. of points: | 1 point                            |
| Cierre - Tipo llave:     | 5 mm double-bit Zamak key included |
| No. of door profiles:    | 2                                  |
| Modelo mural apoyado:    | No                                 |
| Módulo en esquina:       | No                                 |
| Montaje intermedio:      | No                                 |
| Tejadillo inclinado:     | No                                 |

## Materials

|                       |                              |
|-----------------------|------------------------------|
| Lock material:        | Zamak cromado                |
| Plate material:       | Galvanised steel             |
| Seal material:        | Polyurethane                 |
| Acabado:              | Satin finish with Scotch 320 |
| Body thickness (mm):  | 1.5                          |
| Door thickness (mm):  | 1.5                          |
| Plate thickness (mm): | 2                            |

## Maximum loads

|                          |     |
|--------------------------|-----|
| Total maximum load (kg): | 325 |
| Maximum door load (kg):  | 25  |
| Maximum plate load (kg): | 300 |

## Electrical properties

|                      |                   |
|----------------------|-------------------|
| Maximum voltage (V): | 1000 AC / 1500 DC |
|----------------------|-------------------|

### Power dissipation:

Power dissipation P(W) as a function of temperature increase  $\Delta T$  (°C)

| 20    | 25    | 30    | 35    | 40    |
|-------|-------|-------|-------|-------|
| 136.6 | 170.8 | 204.9 | 239.1 | 273.2 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

## Certificates and regulations

## Packaging

|                                                  |                     |
|--------------------------------------------------|---------------------|
| Type d'emballage:                                | BX                  |
| U.M. Embalaje - Unitario:                        | C62                 |
| Minimum amount of sale:                          | 1                   |
| dimensiones_embalaje_unitario_alto_ancho_prof_m: | 0.82 x 0.615 x 0.27 |
| Package weight (kg):                             | 28.249              |
| Peso bruto unitario (kg):                        | 31.073              |

## Codes

|                   |               |
|-------------------|---------------|
| EAN code GETIM13: | 8431044541280 |
| Tariff code:      | 85381000      |
| ETIM 8.0 Code:    | EC000261      |
| Código ETIM 9.0:  | EC000261      |

## Environmental

|                                             |                     |
|---------------------------------------------|---------------------|
| Fecha verificación sustancias SVHC (reach): | 0000-00-00 00:00:00 |
|---------------------------------------------|---------------------|

## Downloads (links)

|                            |                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------|
| Product drawing STP (URL): | <a href="https://ide.es/docs/planos/stp/INX806025.stp">https://ide.es/docs/planos/stp/INX806025.stp</a> |
| Product drawing DXF (URL): | <a href="https://ide.es/docs/planos/dxf/INX806025.dxf">https://ide.es/docs/planos/dxf/INX806025.dxf</a> |
| Product drawing (PDF):     | <a href="https://ide.es/docs/planos/pdf/INX806025.pdf">https://ide.es/docs/planos/pdf/INX806025.pdf</a> |
| Assembly instructions:     | 92890_1                                                                                                 |