

Serie Accessories of circuit breaker

Accessories

Reference : IS363

Disconnecter 63A 3P



Features

Application:	Industrial
Tipo de producto:	Interruptor seccionador
Short-circuit making capacity - Icm (A):	1260
Pollution degree:	2
Terminal connection type:	Cable/connection combs
Short time withstand current - Icw 1s:	12 x In
Utilization category:	AC-22A
Terminal size top/button for cable (mm²):	16-50
Connection:	Top and bottom
Impulse withstand voltage - Uimp (kV):	6
Rated current - In (A):	63
Rated working voltage/Ue (V):	400
Rated insulated voltage/UI (V):	500
Rated frequency (Hz):	50/60
Electrical life items:	4000
Mechanical life items:	10000
Protection degree:	IP20
Apto para instalación en exterior:	No

Certificates and regulations

Norms:	EN 60947-3
--------	------------

Packaging

Type d'emballage:	NE
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.084 x 0.053 x 0.078
Package weight (kg):	0.235
Peso bruto unitario (kg):	0.259

Codes

EAN code GETIM13:	8431044494500
Tariff code:	8536201090
ETIM 8.0 Code:	EC000216
Código ETIM 9.0:	EC000216

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (Links)