

Serie -

-

Reference : RITM20010050



Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Surface
Tipo de producto:	RIT modular

Technical data

Protection degree:	IP55
Resistencia al fuego:	No
Resistance to impact:	IK10

Dimensions

Piece dimensions Height x Width x Depth (mm):	2000 x 1000 x 500
Dim. placa - Alto (mm); Dim. placa - Ancho (mm):	1872 x 896

Additional features

Door/window/lid type:	Opaca única
Reversible door:	Yes
Lock type:	Doble barra 5
Plate:	Yes
Plate type:	Wood
No. of doors:	1

No. locks:	1
Additional Information:	Polyamide GF handle RAL 7016

Materials

Calidad del material:	Rolled steel
Lock material:	Poliamida
Plate material:	Wood
Materiales libres de halógenos:	No
Color:	Grey RAL 7035
Acabado:	Embossed hardened polyester paint
Door thickness (mm):	2
Plate thickness (mm):	18

Electrical properties

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage:	PF
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	2.17 x 0.54 x 1.05
Package weight (kg):	164.502
Peso bruto unitario (kg):	180.953

Codes

EAN code GETIM13:	8431044210704
-------------------	---------------

Tariff code: 85381000

ETIM 8.0 Code: EC000374

Código ETIM 9.0: EC000374

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Assembly instructions: 92871