

Serie -

-

Reference : RITUG20010050/PD

Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Surface
Tipo de producto:	RIT compacto

Technical data

Protection degree:	IP55
Resistencia al fuego:	No
Resistance to impact:	IK10

Dimensions

Piece dimensions Height x Width x Depth (mm):	2000 x 1000 x 500
Dim. placa - Alto (mm); Dim. placa - Ancho (mm):	1872 x 896

Additional features

Door/window/lid type:	Opaca doble
Reversible door:	Yes
Lock type:	Doble barra 5
Plate:	Yes
Plate type:	Wood
No. of doors:	2
No. locks:	1

Materials

Calidad del material:	Galvanised steel
Lock material:	Poliamida
Plate material:	Wood
Materiales libres de halógenos:	No
Color:	Grey RAL 7035
Acabado:	Embossed hardened polyester paint
Door thickness (mm):	2
Plate thickness (mm):	18

Electrical properties

Certificates and regulations

Packaging

Type d'emballage:	PF
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	2.175 x 1.05 x 0.65
Package weight (kg):	158.791
Peso bruto unitario (kg):	174.67

Codes

EAN code GETIM13:	8431044062457
Tariff code:	85381000
ETIM 8.0 Code:	EC000374
Código ETIM 9.0:	EC000374

Environmental



Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Downloads (links)