

Serie -

-

Reference : RTR50608PLAS



Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Flush-fit brick walls
Tipo de producto:	Registro de terminación de red

Technical data

Protection degree:	IP33
Resistencia al fuego:	No
Resistance to impact:	IK07
Glow wire resistance (°C):	650

Dimensions

Piece dimensions Height x Width x Depth (mm):	532 x 670 x 95
hueco_empotrar_alto_ancho_profundo_mm:	525 x 665 x 70

Additional features

Door/window/lid type:	Opaca doble
Reversible door:	No
Lock type:	Puerta a presión
Plate:	No
Tipo de cubierta:	Door

Versión de la cubierta: Notched

No. of doors: 2

Materials

Calidad del material: Polystyrene (PS)

Materiales libres de halógenos: Yes

Color: WhiteRAL 9003

Electrical properties

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 3

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.533 x 0.669 x 0.195

Package weight (kg): 3.491

Peso bruto unitario (kg): 3.84

Codes

EAN code GETIM13: 8431044064963

Tariff code: 85381000

ETIM 8.0 Code: EC000374

Código ETIM 9.0: EC000374

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/RTR50608PLAS.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/RTR50608PLAS.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/RTR50608PLAS.pdf
Assembly instructions:	92918