

Serie -

-

Reference : RTR50608PLASK/PH



Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Flush-fit hollow walls
Tipo de producto:	Registro de terminación de red

Technical data

Protection degree:	IP33
Resistencia al fuego:	No
Resistance to impact:	IK07
Glow wire resistance (°C):	850

Dimensions

Piece dimensions Height x Width x Depth (mm):	532 x 670 x 105
hueco_empotrar_alto_ancho_profundo_mm:	505 x 649 x 72

Additional features

Door/window/lid type:	Opaca doble
Reversible door:	No
Lock type:	Puerta a presión
Plate:	No
Tipo de cubierta:	Door

Versión de la cubierta: Notched

No. of doors: 2

Materials

Base material: ABS

Frame material: Polystyrene (PS)

Door/window/lid material: Polystyrene (PS)

Materiales libres de halógenos: Yes

Base colour: Grey RAL 7035

Frame color: WhiteRAL 9003

Door color: WhiteRAL 9003

Electrical properties

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 3

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.65 x 0.41 x 0.53

Package weight (kg): 3.715

Peso bruto unitario (kg): 4.086

Codes

EAN code GETIM13: 8431044287249

Tariff code: 85381000

ETIM 8.0 Code: EC000374

Código ETIM 9.0: EC000374

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/RTR50608PLASKPH.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/RTR50608PLASKPH.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/RTR50608PLASKPH.pdf>

Assembly instructions: 92956