

Serie -

-

Reference : RTR50608PME/PH



Features

Application:	Telecommunications
Apto para instalación en exterior:	No
Type of installation:	Flush-fit hollow walls
Tipo de producto:	Registro de terminación de red

Technical data

Protection degree:	IP33
Resistencia al fuego:	No
Resistance to impact:	IK07
Glow wire resistance (°C):	850

Dimensions

Piece dimensions Height x Width x Depth (mm):	627 x 775 x 95
hueco_empotrar_alto_ancho_profundo_mm:	597 x 745 x 95

Additional features

Door/window/lid type:	Opaca doble
Reversible door:	No
Lock type:	Cierre a presión
Plate:	No
No. of doors:	2

No. locks: 2

Materials

Base material: ABS

Door/window/lid material: Rolled steel

Lock material: ABS

Materiales libres de halógenos: Yes

Base colour: Grey RAL 7035

Door color: WhiteRAL 9003

Acabado: Embossed hardened polyester paint

Electrical properties

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208; UNE-EN 60670-1

Packaging

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.399 x 0.644 x 0.113

Package weight (kg): 7.227

Peso bruto unitario (kg): 7.95

Codes

EAN code GETIM13: 8431044410128

Tariff code: 85381000

ETIM 8.0 Code: EC000374

Código ETIM 9.0:

EC000374

Environmental

Fecha verificación sustancias SVHC (reach):

0000-00-00 00:00:00

Packaging:

100% recyclable cardboard

Downloads (links)

Product drawing STP (URL):

<https://ide.es/docs/planos/stp/RTR50608PMEPH.stp>

Product drawing DXF (URL):

<https://ide.es/docs/planos/dxf/RTR50608PMEPH.dxf>

Product drawing (PDF):

<https://ide.es/docs/planos/pdf/RTR50608PMEPH.pdf>

Assembly instructions:

91098