

Serie Star Complet

IP65 Boxes with assembled and wired power sockets

Reference : SV6302/P

IP65 1x6 mod. Box with power sockets and wired protections



Features

Application:	Industrial (Watertight and distribution enclosures),Construction
Apto para instalación en exterior:	Yes
Type of installation:	Surface
Calidad del material:	ABS

Modular capacity

Capacity/Number of modules:	1x6
Number of rows:	1

Components:

Nº	Description	IP	Poles	Current (A)	Voltage (V)
1	Sloping flush-fit socket	44	3P+T	16	400
2	Schuko-type sockets	54	2P+TT	16	230

Protections:

Nº	Description	Curve	Rated breaking capacity (kA)	Poles	Current (A)	Voltage (V)
1	MCB miniature circuit breaker	C	10	3P	16	400
1	MCB miniature circuit breaker	C	10	2P	16	230

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Box glow wire resistance (°C):	650
Cabinet pressure test (°C):	70
Ball pressure in sockets (°C):	125
Double insulation:	Class II

Dimensions

Piece dimensions Height x Width x Depth (mm):	436 x 142 x 180
Upper cable entry (mm):	2xM20-1xM40
Bottom cable entry (mm):	2xM20-1xM40
Rear oblong:	2xOB25x25

Additional features

Emergency button:	No
Door/window/lid type:	Transparente
Reversible door:	No
UV protection:	Yes
Lock type:	Cierre a presión
No. locks:	1
Tipo de cubierta:	Door
Versión de la cubierta:	Closed
Sealable:	Yes
Enlazable:	Yes
Incorpora Raíl DIN:	Yes

Materials

Materiales libres de halógenos:	Yes
Base material:	ABS
Frame material:	ABS
Door/window/lid material:	Polycarbonate (PC)
Lock material:	Resina acetálica
Color:	Grey RAL 7035
Base colour:	Grey
Frame color:	Grey
Door color:	Tinted

Electrical properties

Voltage (V):	230/400
Intensidad nominal (A):	32

Certificates and regulations

Directive:	2014/35/EU
Norms:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Suministro:	- Supplied fully assembled according to the specifications of each reference, protected with shrink wrap and packed in multiple cardboard packaging according to the number of units ordered. - With certificate of conformity, description, number of socket outlets and protection devices, and the corresponding single-line diagram.
Type d'emballage:	WR
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.386 x 0.388 x 0.586
Package weight (kg):	2.297
Peso bruto unitario (kg):	2.527

Codes

EAN code GETIM13:	8431044120157
Tariff code:	85371098
ETIM 8.0 Code:	EC000379
Código ETIM 9.0:	EC000379

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (links)

Assembly instructions:

93064