

Serie Pryma Complet

IP67 Boxes with assembled and wired power sockets

Reference : V8MA2/P67

IP67 1x9 mod. Box with power sockets and wired protections



Features

Application:	Industrial (Watertight and distribution enclosures),Construction
Apto para instalación en exterior:	Yes
Type of installation:	Surface
Calidad del material:	ABS

Modular capacity

Capacity/Number of modules:	1x9
Number of rows:	1

Components:

Nº	Description	IP	Poles	Current (A)	Voltage (V)
1	Sloping flush-fit socket	67	3P+T	16	400
1	Sloping flush-fit socket	67	3P+T	32	400
2	Schuko-type sockets	67	2P+TT	16	230

Protections:

Nº	Description	Curve	Rated breaking capacity (kA)	Poles	Current (A)	Voltage (V)
1	MCB miniature circuit breaker	C	10	3P	16	400
1	MCB miniature circuit breaker	C	10	3P	32	400
1	MCB miniature circuit breaker	C	10	2P	16	230

Technical data

Protection degree:	IP67
Resistance to impact:	IK08
Glow wire resistance (°C):	650
Cabinet pressure test (°C):	70

Ball pressure in sockets (°C):	125
Double insulation:	Class II

Dimensions

Piece dimensions Height x Width x Depth (mm):	369 x 222 x 190
---	-----------------

Additional features

Emergency button:	No
Door/window/lid type:	Transparente
Sujeción de puerta/tapa/ventana:	Screw-on
Reversible door:	No
UV protection:	Yes
Lock type:	Con tornillos
Tipo de cubierta:	Door
Versión de la cubierta:	Closed
Sealable:	Yes
Enlazable:	No
Incorpora Raíl DIN:	Yes

Materials

Materiales libres de halógenos:	Yes
Base material:	ABS
Frame material:	ABS
Door/window/lid material:	Polycarbonate (PC)
Color:	Grey RAL 7035
Base colour:	Grey
Frame color:	Grey
Door color:	Tinted

Electrical properties

Voltage (V):	230/400
--------------	---------

Intensidad nominal (A): 63

Certificates and regulations

Directive: 2014/35/EU

Norms: UNE-EN 62208, UNE-EN 61439-1

Packaging

Suministro:

- Supplied fully assembled according to the specifications of each reference, protected with shrink wrap and packed in multiple cardboard packaging according to the number of units ordered.
- With certificate of conformity, description, number of socket outlets and protection devices, and the corresponding single-line diagram.

Type d'emballage: WR

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.386 x 0.388 x 0.586

Package weight (kg): 3.204

Peso bruto unitario (kg): 3.525

Codes

EAN code GETIM13: 8431044235233

Tariff code: 85371098

ETIM 8.0 Code: EC000379

Código ETIM 9.0: EC000379

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (links)

Assembly instructions: 93064