

Serie Ventilation

Ventilation

Reference : VF245DC

Fan with filter 245 M3/h 24V DC IP54



Features

Apto para instalación en exterior:	No
Tipo de producto:	DC con filtro

Additional features

Relative humidity range (%):	0-95
Electrical connection:	Terminal
Device mounting:	Quick clip or screws

Ventilation

Voltage (V):	24
Air flow with filter (m3/h):	245
Operating temperature (°C):	-20/+70
Filtration efficiency (%):	? 73
Service at 40 °C (h):	50
Noise level (dB):	48
Current consumption (A):	0,50
Energy consumption (W):	12
Static pressure (Pa):	95
Overcurrent protection:	Impedancia
Direction of flow:	De fuera hacia dentro
Reversible:	Yes
Bearing:	Ball bearing

Heating

Regulating

Technical data

Protection degree:	IP54
--------------------	------

Materials

Calidad del material:	ABS
Filtro:	Yes
Filter material (g/m3):	Fibra de nylon 150
Seal material:	Polyurethane
Materiales libres de halógenos:	No
Color:	Grey RAL 7035

Dimensions

Piece dimensions Height x Width x Depth (mm):	255 x 255 x 116
Cut-off dimensions (mm):	224x224
Thickness of the cabinet wall (mm):	2

Certificates and regulations

Directive:	2014/35/EU
Norms:	IEC 62208; IEC 61439-1

Packaging

Suministro:	Supplied in individual cardboard packaging.
Type d'emballage:	BX

U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.255 x 0.255 x 0.117
Package weight (kg):	1.3
Peso bruto unitario (kg):	1.43

Codes

EAN code GETIM13:	8431044250359
Tariff code:	84145995
ETIM 8.0 Code:	EC000320
Código ETIM 9.0:	EC000320

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (Links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/VF245DC.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/VF245DC.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/VF245DC.pdf
Assembly instructions:	93061