

Serie Ventilation

Ventilation

Reference : VF280AC

Fan with filter 280 M3/h 230V AC IP54



Features

Apto para instalación en exterior:	No
Tipo de producto:	AC con filtro

Additional features

Relative humidity range (%):	0-95
Electrical connection:	Terminal
Device mounting:	Quick clip or screws

Ventilation

Voltage (V):	230
Voltage (Hz):	50-60
Air flow with filter (m3/h):	280-320
Operating temperature (°C):	-20/+70
Filtration efficiency (%):	? 73
Service at 40 °C (h):	50
Noise level (dB):	48
Current consumption (A):	0,26-0,24
Energy consumption (W):	41
Static pressure (Pa):	120-135
Overcurrent protection:	Impedancia
Direction of flow:	De fuera hacia dentro
Reversible:	Yes

Bearing: Ball bearing

Heating

Regulating

Technical data

Protection degree: IP54

Materials

Calidad del material: ABS

Filtro: Yes

Filter material (g/m3): Fibra de nylon 150

Seal material: Polyurethane

Materiales libres de halógenos: No

Color: Grey RAL 7035

Dimensions

Piece dimensions Height x Width x Depth (mm): 255 x 255 x 116

Cut-off dimensions (mm): 224x224

Thickness of the cabinet wall (mm): 2

Certificates and regulations

Directive: 2014/35/EU

Norms: IEC 62208; IEC 61439-1

Packaging

Suministro: Supplied in individual cardboard packaging.

Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.255 x 0.255 x 0.117
Package weight (kg):	1.47
Peso bruto unitario (kg):	1.617

Codes

EAN code GETIM13:	8431044250199
Tariff code:	84145995
ETIM 8.0 Code:	EC000320
Código ETIM 9.0:	EC000320

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (Links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/VF280AC.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/VF280AC.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/VF280AC.pdf
Assembly instructions:	93061