Serie Ventilation

Ventilation

Reference : VF280AC/115

Fan with filter 280 m³/h 115V AC IP54



Features

Apto para instalación en exterior:	No
Tipo de producto:	Filter fan (AC)

Additional features

Relative humidity range (%):	0-95
Electrical connection:	Terminal
Device mounting:	Quick clip or screws

Ventilation

Voltage (V):	115
Air flow with filter (m3/h):	280-320
Operating temperature (ºC):	-20/+70
Filtration efficiency (%):	? 73
Service at 40 °C (h):	50
Noise level (dB):	48
Current consumption (A):	0,48-0,46
Energy consumption (W):	41
Static pressure (Pa):	120-135
Overcurrent protection:	Impedancia
Direction of flow:	De fuera hacia dentro
Reversible:	Yes
Bearing:	Ball bearing

Heating

Regulating

Technical data

Protection degree:	IP54

Materials

Calidad del material:	ABS
Filtro:	Yes
Filter material (g/m3):	Nylon fibre 150
Seal material:	Polyurethane
Materiales libres de halógenos:	No
Color:	Grey RAL 7035

Dimensions

Piece dimensions - HxWxD (mm):	255 x 255 x 116
Cut-off dimensions (mm):	224x224
Thickness of the cabinet wall (mm):	2

Certificates and regulations

Directive:	2014/35/EU
Norms:	IEC 62208; IEC 61439-1

Packaging

Suministro:	Supplied in individual cardboard packaging
Type d'emballage:	BX

U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
Individual packaging dimensions - HxWxD (m):	0.255 x 0.255 x 0.117
Package weight (kg):	1.94
Peso bruto unitario (kg):	2.134

Codes

EAN code GETIM13:	8431044404370
Tariff code:	84145915
ETIM 8.0 Code:	EC000320
Código ETIM 9.0:	EC000320

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (Links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/VF280AC115.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/VF280AC115.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/VF280AC115.pdf
Assembly instructions:	93061