

Serie Ventilation

Ventilation

Reference : VF92AC

Fan with filter 92 M3/h 230V AC IP54



Features

Apto para instalación en exterior:	No
Tipo de producto:	AC con filtro

Additional features

Relative humidity range (%):	0-95
Electrical connection:	Terminal

Ventilation

Voltage (V):	230
Voltage (Hz):	50-60
Air flow with filter (m3/h):	92-107
Operating temperature (°C):	-20/+65
Filtration efficiency (%):	? 73
Service at 40 °C (h):	50
Noise level (dB):	32
Current consumption (A):	0,12-0,10
Energy consumption (W):	19
Static pressure (Pa):	32-39
Overcurrent protection:	Impedancia
Direction of flow:	De fuera hacia dentro
Reversible:	Yes
Bearing:	Ball bearing

Heating

Regulating

Technical data

Protection degree:	IP54
--------------------	------

Materials

Calidad del material:	ABS
Filtro:	Yes
Filter material (g/m3):	Fibra de nylon 150
Seal material:	Polyurethane
Materiales libres de halógenos:	No
Color:	Grey RAL 7035

Dimensions

Piece dimensions Height x Width x Depth (mm):	148.5 x 148.5 x 68.5
Cut-off dimensions (mm):	124x124
Thickness of the cabinet wall (mm):	2

Certificates and regulations

Directive:	2014/35/EU
Norms:	IEC 62208; IEC 61439-1

Packaging

Suministro:	Supplied in individual cardboard packaging.
Type d'emballage:	BX

U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.149 x 0.149 x 0.069
Package weight (kg):	0.7
Peso bruto unitario (kg):	0.77

Codes

EAN code GETIM13:	8431044250175
Tariff code:	84145995
ETIM 8.0 Code:	EC000320
Código ETIM 9.0:	EC000320

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (Links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/VF92AC.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/VF92AC.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/VF92AC.pdf
Assembly instructions:	93061