

Serie Ventilation

Ventilation

Reference : VT1020

Ceiling fan 1020 M3/h 230V AC IP54



Features

Apto para instalación en exterior: No

Additional features

Relative humidity range (%): 0-95

Electrical connection: Cable

Ventilation

Voltage (V): 230

Voltage (Hz): 50-60

Air flow with filter (m3/h): 1020-1140

Operating temperature (°C): -30/+80

Service at 40 °C (h): 50

Noise level (dB): 62

Current consumption (A): 0,60-0,74

Energy consumption (W): 131

Static pressure (Pa): 430-585

Overcurrent protection: Térmica

Direction of flow: De dentro hacia fuera

Reversible: No

Bearing: Ball bearing

Heating

Regulating

Technical data

Protection degree:	IP54
--------------------	------

Materials

Calidad del material:	ABS,Iron
Filtro:	No
Seal material:	Polyurethane
Materiales libres de halógenos:	No
Color:	Grey RAL 7035

Dimensions

Piece dimensions Height x Width x Depth (mm):	310 x 310 x 140
Cut-off dimensions (mm):	Ø220

Certificates and regulations

Directive:	2014/35/EU
Norms:	IEC 62208; IEC 61439-1

Packaging

Suministro:	Supplied in individual cardboard packaging.
Type d'emballage:	BX
U.M. Embalaje - Unitario:	C62
Minimum amount of sale:	1
dimensiones_embalaje_unitario_alto_ancho_prof_m:	0.31 x 0.31 x 0.14

Package weight (kg):	5.7
Peso bruto unitario (kg):	6.27

Codes

EAN code GETIM13:	8431044250380
Tariff code:	84145995
ETIM 8.0 Code:	EC000320
Código ETIM 9.0:	EC000320

Environmental

Fecha verificación sustancias SVHC (reach):	0000-00-00 00:00:00
Packaging:	100% recyclable cardboard

Downloads (Links)

Product drawing STP (URL):	https://ide.es/docs/planos/stp/VT1020.stp
Product drawing DXF (URL):	https://ide.es/docs/planos/dxf/VT1020.dxf
Product drawing (PDF):	https://ide.es/docs/planos/pdf/VT1020.pdf
Assembly instructions:	93062